

INDUSTRIAL COMPONENT DATA

3RT2017-1QB42 SIEMENS power contactor, AC-3 12 A, 5.5 kW / 400 V 1 NC, 24 V DC 0.7-1.25* US, with varistor p..

Brand: SIEMENS | Manufacturer Part Number: 3RT2017-1QB42



Manufacturer	SIEMENS
MPN / Reference	3RT2017-1QB42
Catalog number	20171
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-7BC93FAC1A
Generated	2026-08-04

Product Overview

power contactor, AC-3 12 A, 5.5 kW / 400 V 1 NC, 24 V DC 0.7-1.25* US, with varistor plugged on, 3-pole size S00, screw terminal not expandable with auxiliary switch

SIRIUS Innovations Contactor coupling, AC-3, 5, 5KW/400V 1NC, DC 24V, 0, 7...1, 25*US, with diode, S00, screw connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

power contactor, AC-3 12 A, 5.5 kW / 400 V 1 NC, 24 V DC 0.7-1.25* US, with varistor plugged on, 3-pole size S00, screw terminal not expandable with auxiliary switch

product brand name SIRIUS

product designation Coupling contactor

product type designation 3RT2

General technical data

size of contactor S00

product extension

? function module for communication No

? auxiliary switch No

power loss [W] for rated value of the current

? at AC in hot operating state 3.6 W
? at AC in hot operating state per pole 1.2 W
? without load current share typical 2.8 W
insulation voltage
? of main circuit with degree of pollution 3 rated value 690 V
? of auxiliary circuit with degree of pollution 3 rated value 690 V
surge voltage resistance
? of main circuit rated value 6 kV
? of auxiliary circuit rated value 6 kV
maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1 400 V
shock resistance at rectangular impulse
? at DC 7.3g / 5 ms, 4.7g / 10 ms
shock resistance with sine pulse
? at DC 11.4g / 5 ms, 7.3g / 10 ms
mechanical service life (switching cycles)
? of contactor typical 30 000 000
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -55 ... +80 °C
relative humidity minimum 10 %
relative humidity at 55 °C according to IEC 60068-2-30 maximum 95 %...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT2017-1QB42 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.