

INDUSTRIAL COMPONENT DATA

3RT2018-2BB42-0CC0 SIEMENS Power contactor, AC-3 16 A, 7.5 kW / 400 V 1 NC, 24 V DC communication-capable, 3..

Brand: SIEMENS | Manufacturer Part Number: 3RT2018-2BB42-0CC0



Manufacturer	SIEMENS
MPN / Reference	3RT2018-2BB42-0CC0
Catalog number	20182
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-CB61120C2C
Generated	2026-08-04

Product Overview

Power contactor, AC-3 16 A, 7.5 kW / 400 V 1 NC, 24 V DC communication-capable, 3-pole Size S00, Spring-type terminals

SIRIUS Innovations Contactor, AC-3, 7, 5KW/400V, 1NC, DC 24V, APTO COM., S00 spring connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors
--------------	--

Additional Product Information

Technical data

Power contactor, AC-3 16 A, 7.5 kW / 400 V 1 NC, 24 V DC communication-capable, 3-pole Size S00, Spring-type terminals

product brand name SIRIUS

product designation Power contactor

product type designation 3RT2

General technical data

size of contactor S00

product extension

? function module for communication Yes

? auxiliary switch Yes

power loss [W] for rated value of the current

? at AC in hot operating state 6.6 W
? at AC in hot operating state per pole 2.2 W
? without load current share typical 4 W
insulation voltage
? of main circuit with degree of pollution 3 rated value 690 V
? of auxiliary circuit with degree of pollution 3 rated value 690 V
surge voltage resistance
? of main circuit rated value 6 kV
? of auxiliary circuit rated value 6 kV
maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1 400 V
shock resistance at rectangular impulse
? at DC 7.3g / 5 ms, 4.7g / 10 ms
shock resistance with sine pulse
? at DC 11.4g / 5 ms, 7.3g / 10 ms
mechanical service life (switching cycles)
? of contactor typical 30 000 000
? of the contactor with added electronically optimized auxiliary switch block typical 5 000 000
? of the contactor with added auxiliary switch block typical 10 000 000
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during sto...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT2018-2BB42-0CC0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.