

**INDUSTRIAL COMPONENT DATA**

# 3RT2035-3KB40 SIEMENS power contactor, AC-3 40 A, 18.5 kW / 400 V 1 NO + 1 NC, 24 V DC with varistor, 3-pole..

Brand: SIEMENS | Manufacturer Part Number: 3RT2035-3KB40



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 3RT2035-3KB40                 |
| Catalog number  | 20353                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-5832207B97                 |
| Generated       | 2026-08-06                    |

## Product Overview

power contactor, AC-3 40 A, 18.5 kW / 400 V 1 NO + 1 NC, 24 V DC with varistor, 3-pole, Size S2, Spring-type terminal  
Suitable for 2 A PLC outputs

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                    |
|--------------|--------------------------------------------------------------------|
| Catalog path | SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors |
|--------------|--------------------------------------------------------------------|

## Additional Product Information

**Technical data**

power contactor, AC-3 40 A, 18.5 kW / 400 V 1 NO + 1 NC, 24 V DC with varistor, 3-pole, Size S2, Spring-type terminal  
Suitable for 2 A PLC outputs

product brand name SIRIUS

product designation Coupling contactor

product type designation 3RT2

**General technical data**

size of contactor S2

product extension

? function module for communication No

? auxiliary switch Yes

power loss [W] for rated value of the current

? at AC in hot operating state 6.6 W

? at AC in hot operating state per pole 2.2 W

? without load current share typical 1 W

insulation voltage

? of main circuit with degree of pollution 3 rated value 690 V

? of auxiliary circuit with degree of pollution 3 rated value 690 V

surge voltage resistance

? of main circuit rated value 6 kV

? of auxiliary circuit rated value 6 kV

maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1 400 V

shock resistance at rectangular impulse

? at DC 7.7g / 5 ms, 4.5g / 10 ms

shock resistance with sine pulse

? at DC 12g / 5 ms, 7g / 10 ms

mechanical service life (switching cycles)

? of contactor typical 10 000 000

? of the contactor with added electronically optimized auxiliary switch block typical 5 000 000

? of the contactor with added auxiliary switch block typical 10 000 000

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 10/01/2014

Ambient conditions

installation altitude at height above sea level maximum 2 000 m

ambient temperature

? during operation -2...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT2035-3KB40 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.