

**INDUSTRIAL COMPONENT DATA**

# 3RT2037-3NB34-3MA0 SIEMENS Power contactor, AC-3 65 A, 30 kW / 400 V 2 NO + 2 NC, 20-33 V AC/DC with varisto..

Brand: SIEMENS | Manufacturer Part Number: 3RT2037-3NB34-3MA0



|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | SIEMENS                       |
| MPN / Reference | 3RT2037-3NB34-3MA0            |
| Catalog number  | 20373                         |
| Category        | Power contactor, AC switching |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-39B4090AE4                 |
| Generated       | 2026-08-05                    |

## Product Overview

Power contactor, AC-3 65 A, 30 kW / 400 V 2 NO + 2 NC, 20-33 V AC/DC with varistor 3-pole, size S2 spring-type terminal, Perm. mounted auxiliary switch

CONTACTOR 3 POLES, SIZE S2, 65A AC-3, AC/DC 20-33V, 30KW / 400V, 2NA+2NC, NON-REMOVABLE, SPRING TERMINALS. Manufactured to order. Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

## Additional Product Information

**Technical data**

Power contactor, AC-3 65 A, 30 kW / 400 V 2 NO + 2 NC, 20-33 V AC/DC with varistor 3-pole, size S2 spring-type terminal, Perm. mounted auxiliary switch

product brand name SIRIUS

product designation Power contactor

product type designation 3RT2

**General technical data**

size of contactor S2

product extension

? function module for communication No

? auxiliary switch No

power loss [W] for rated value of the current

? at AC in hot operating state 11.4 W  
? at AC in hot operating state per pole 3.8 W  
? without load current share typical 2 W  
insulation voltage  
? of main circuit with degree of pollution 3 rated value 690 V  
? of auxiliary circuit with degree of pollution 3 rated value 690 V  
surge voltage resistance  
? of main circuit rated value 6 kV  
? of auxiliary circuit rated value 6 kV  
maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1 400 V  
shock resistance at rectangular impulse  
? at AC 6.1g / 5 ms, 3.7g / 10 ms  
? at DC 6.1g / 5 ms, 3.7g / 10 ms  
shock resistance with sine pulse  
? at AC 9.6g / 5 ms, 5.8g / 10 ms  
? at DC 9.6g / 5 ms, 5.8g / 10 ms  
mechanical service life (switching cycles)  
? of contactor typical 10 000 000  
? of the contactor with added electronically optimized auxiliary switch block typical 5 000 000  
? of the contactor with added auxiliary switch block typical 10 000 000  
reference code according to IEC 81346-2 Q  
Substance Prohibitance (Date) 10/01/2014  
Ambient conditions  
installation altitude at height....

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT2037-3NB34-3MA0 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.