

INDUSTRIAL COMPONENT DATA

3RT2038-1AG60 SIEMENS Contactor, AC-3, 37 kW / 400 V, 1 NO + 1 NC, 100 V AC, 50Hz / 100 ... 110 V, 60 Hz, 3-..

Brand: SIEMENS | Manufacturer Part Number: 3RT2038-1AG60



Manufacturer	SIEMENS
MPN / Reference	3RT2038-1AG60
Catalog number	20381
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-4C5E7368E0
Generated	2026-08-06

Product Overview

Contactor, AC-3, 37 kW / 400 V, 1 NO + 1 NC, 100 V AC, 50Hz / 100 ... 110 V, 60 Hz, 3-pole, Size S2, screw terminal
 CONTACTOR 3 POLES, SIZE S2, 80A AC-3, AC 100V 50HZ, 37KW / 400V, 1NA+1NC, SCREW TERMINALS.
 Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors**

Additional Product Information

Technical data

Contactor, AC-3, 37 kW / 400 V, 1 NO + 1 NC, 100 V AC, 50Hz / 100 ... 110 V, 60 Hz, 3-pole, Size S2, screw terminal
 product brand name SIRIUS

product designation Power contactor

product type designation 3RT2

General technical data

size of contactor S2

product extension

? function module for communication No

? auxiliary switch Yes

power loss [W] for rated value of the current

? at AC in hot operating state 17.1 W

? at AC in hot operating state per pole 5.7 W

? without load current share typical 18.5 W

insulation voltage

? of main circuit with degree of pollution 3 rated value 690 V

? of auxiliary circuit with degree of pollution 3 rated value 690 V

surge voltage resistance

? of main circuit rated value 6 kV

? of auxiliary circuit rated value 6 kV

maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1 400 V

shock resistance at rectangular impulse

? at AC 11.8g / 5 ms, 7.4g / 10 ms

shock resistance with sine pulse

? at AC 18.5g / 5 ms, 11.6g / 10 ms

mechanical service life (switching cycles)

? of contactor typical 10 000 000

? of the contactor with added electronically optimized auxiliary switch block typical 5 000 000

? of the contactor with added auxiliary switch block typical 10 000 000

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 10/01/2014

Ambient conditions

installation altitude at height above sea level maximum 2 000 m

ambient temperature

? during operation -25 ... +60 °C

? during st...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT2038-1AG60 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.