

INDUSTRIAL COMPONENT DATA

3RT2317-2AP00 SIEMENS Contactor, 4 NO, AC-1: 22 A 230 V AC, 50 / 60 Hz, 4-pole, 4 NO, Size S00, Spring-type ..

Brand: SIEMENS | Manufacturer Part Number: 3RT2317-2AP00



Manufacturer	SIEMENS
MPN / Reference	3RT2317-2AP00
Catalog number	23172
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-F04DAAACFC
Generated	2026-08-05

Product Overview

Contactor, AC-1, 22 A/400 V/40 °C, S00, 4-pole, 230 V AC, 50/60 Hz, Spring-type terminal

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors
--------------	--

Additional Product Information

Technical data

Contactor, AC-1, 22 A/400 V/40 °C, S00, 4-pole, 230 V AC, 50/60 Hz, Spring-type terminal

product brand name SIRIUS

product designation Contactor

product type designation 3RT23

General technical data

size of contactor S00

product extension

? function module for communication No

? auxiliary switch Yes

power loss [W] for rated value of the current

? at AC in hot operating state 6.4 W

? at AC in hot operating state per pole 1.6 W

insulation voltage

? of main circuit with degree of pollution 3 rated value 690 V

? of the auxiliary and control circuit with degree of pollution 3 rated value 690 V
surge voltage resistance
? of main circuit rated value 6 kV
? of auxiliary circuit rated value 6 kV
shock resistance at rectangular impulse
? at AC 7,3g / 5 ms, 4,7g / 10 ms
shock resistance with sine pulse
? at AC 11,4g / 5 ms, 7,3g / 10 ms
mechanical service life (switching cycles)
? of contactor typical 30 000 000
? of the contactor with added auxiliary switch block typical 10 000 000
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -55 ... +80 °C
relative humidity minimum 10 %
relative humidity at 55 °C according to IEC 60068-2-30 maximum 95 %
Main circuit
number of poles for main current circuit 4
number of NO contacts for main contacts 4
operational current
? at AC-1 at 400 V at ambien...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT2317-2AP00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.