

INDUSTRIAL COMPONENT DATA

3RT2446-1NB30 SIEMENS Contactor, AC-1, 140 A/690 V/40 °C, S3, 3-pole, 20-33 V AC/DC, with varistor, 1 NO+1 N..

Brand: SIEMENS | Manufacturer Part Number: 3RT2446-1NB30



Manufacturer	SIEMENS
MPN / Reference	3RT2446-1NB30
Catalog number	24461
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-F60F2A20B5
Generated	2026-08-06

Product Overview

Contactor, AC-1, 140 A/690 V/40 °C, S3, 3-pole, 20-33 V AC/DC, with varistor, 1 NO+1 NC, box terminal/screw terminal
 CONTACTOR, AC1:140A, 20-33 V AC/DC, 3-POLE, 3NO, SIZE: S3, SCREW TERMINALS 1NO+1NC, VARISTOR
 INTEGR..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors
--------------	--

Additional Product Information

Technical data

Contactor, AC-1, 140 A/690 V/40 °C, S3, 3-pole, 20-33 V AC/DC, with varistor, 1 NO+1 NC, box terminal/screw terminal

product brand name SIRIUS

product designation Contactor

product type designation 3RT24

General technical data

size of contactor S3

product extension

? function module for communication No

? auxiliary switch Yes

power loss [W] for rated value of the current

? at AC in hot operating state 29.4 W

? at AC in hot operating state per pole 9.8 W

? without load current share typical 1.8 W
insulation voltage
? of main circuit with degree of pollution 3 rated value 1 000 V
? of auxiliary circuit with degree of pollution 3 rated value 690 V
surge voltage resistance
? of main circuit rated value 8 kV
? of auxiliary circuit rated value 6 kV
shock resistance at rectangular impulse
? at AC 6.7 g / 5 ms, 4.0 g / 10 ms
? at DC 6.7 g / 5 ms, 4.0 g / 10 ms
shock resistance with sine pulse
? at AC 10.6 g / 5 ms, 6.3 g / 10 ms
? at DC 10.6 g / 5 ms, 6.3 g / 10 ms
mechanical service life (switching cycles)
? of contactor typical 10 000 000
? of the contactor with added electronically optimized auxiliary switch block typical 5 000 000
? of the contactor with added auxiliary switch block typical 10 000 000
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 04/27/2017
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -55 ... +80 °C
relative humidity...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT2446-1NB30 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.