

INDUSTRIAL COMPONENT DATA

3RT2526-2BM40 SIEMENS Power contactor, AC-3 25 A, 11 kW / 400 V 2 NO + 2 NC 220 V DC 4-pole size S0 Spring-t..

Brand: SIEMENS | Manufacturer Part Number: 3RT2526-2BM40



Manufacturer	SIEMENS
MPN / Reference	3RT2526-2BM40
Catalog number	25262
Category	Power contactor, AC switching
Minimum order	1 Pcs
Document ID	EO-979B05BAE9
Generated	2026-08-05

Product Overview

Power contactor, AC-3 25 A, 11 kW / 400 V 2 NO + 2 NC 220 V DC 4-pole size S0 Spring-type terminals 1 NO + 1 NC integrated

SIRIUS Innovations Contactor, AC-3, 11KW/400V, AC-1 40A, 1NA+1NC, DC 220V, 4-pole, 2NA+2NC, S0, spring connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Contactors for switching motors
--------------	--

Additional Product Information

Technical data

Power contactor, AC-3 25 A, 11 kW / 400 V 2 NO + 2 NC 220 V DC 4-pole size S0 Spring-type terminals 1 NO + 1 NC integrated

product brand name SIRIUS

product designation contactor

product type designation 3RT25

General technical data

size of contactor S0

product extension

? function module for communication No

? auxiliary switch Yes

insulation voltage

? of main circuit with degree of pollution 3 rated value 690 V
? of auxiliary circuit with degree of pollution 3 rated value 690 V
surge voltage resistance
? of main circuit rated value 6 kV
? of auxiliary circuit rated value 6 kV
maximum permissible voltage for safe isolation between coil and main contacts according to EN 60947-1 400 V
shock resistance at rectangular impulse
? at DC 10g / 5 ms, 7,5g / 10 ms
shock resistance with sine pulse
? at DC 15g / 5 ms, 10g / 10 ms
mechanical service life (switching cycles)
? of contactor typical 10 000 000
? of the contactor with added electronically optimized auxiliary switch block typical 5 000 000
? of the contactor with added auxiliary switch block typical 10 000 000
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -55 ... +80 °C
relative humidity minimum 10 %
relative humidity at 55 °C according to IEC 60068-2-30 maximum 95 %
Main circuit
number of poles for main current circuit 4
nu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RT2526-2BM40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.