

**INDUSTRIAL COMPONENT DATA**

# 3RU2116-0DB1 SIEMENS Overload relay 0.22...0.32 A Thermal For motor protection Size S00, Class 10 Stand-alon..

Brand: SIEMENS | Manufacturer Part Number: 3RU2116-0DB1



|                 |                        |
|-----------------|------------------------|
| Manufacturer    | SIEMENS                |
| MPN / Reference | 3RU2116-0DB1           |
| Catalog number  | 21160                  |
| Category        | Thermal overload relay |
| Minimum order   | 1 Pcs                  |
| Document ID     | EO-A7529747EE          |
| Generated       | 2026-08-03             |

## Product Overview

Overload relay 0.22...0.32 A Thermal For motor protection Size S00, Class 10 Stand-alone installation Main circuit: Screw Auxiliary circuit: Screw Manual-Automatic-Reset  
SIRIUS Innovations Thermal overload relay, motor protection 0, 22...0, 32 A, S00, Class 10, independent assembly screw connection. Manufactured to order. Non-Cancelable Non-Returnable.

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Thermal relays**

## Additional Product Information

**Technical data**

Overload relay 0.22...0.32 A Thermal For motor protection Size S00, Class 10 Stand-alone installation Main circuit: Screw Auxiliary circuit: Screw Manual-Automatic-Reset  
product brand name SIRIUS  
product designation thermal overload relay  
product type designation 3RU2  
General technical data  
size of overload relay S00  
size of contactor can be combined company-specific S00  
power loss [W] for rated value of the current at AC in hot operating state 4.8 W  
? per pole 1.6 W  
insulation voltage with degree of pollution 3 at AC rated value 690 V

surge voltage resistance rated value 6 kV  
maximum permissible voltage for safe isolation in networks with grounded star point  
? between auxiliary and auxiliary circuit 440 V  
? between auxiliary and auxiliary circuit 440 V  
? between main and auxiliary circuit 440 V  
? between main and auxiliary circuit 440 V  
shock resistance according to IEC 60068-2-27 8g / 11 ms  
type of protection according to ATEX directive 2014/34/EU Ex II (2) GD  
certificate of suitability according to ATEX directive 2014/34/EU DMT 98 ATEX G 001  
reference code according to IEC 81346-2 F  
Substance Prohibitance (Date) 10/01/2009  
Ambient conditions  
installation altitude at height above sea level maximum 2 000 m  
ambient temperature  
? during operation -40 ... +70 °C  
? during storage -55 ... +80 °C  
? during transport -55 ... +80 °C  
temperature compensation -40 ... +60 °C  
relative humidity during operation 10 ... 95 %  
Main circuit  
number of poles for main current circ...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RU2116-0DB1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.