

INDUSTRIAL COMPONENT DATA

3RU2116-1JB1 SIEMENS Overload relay 7.0...10 A Thermal For motor protection Size S00, Class 10 Stand-alone i..

Brand: SIEMENS | Manufacturer Part Number: 3RU2116-1JB1



Manufacturer	SIEMENS
MPN / Reference	3RU2116-1JB1
Catalog number	21161
Category	Thermal overload relay
Minimum order	1 Pcs
Document ID	EO-C9A4B71533
Generated	2026-08-04

Product Overview

Overload relay 7.0...10 A Thermal For motor protection Size S00, Class 10 Stand-alone installation Main circuit: Screw Auxiliary circuit: Screw Manual-Automatic-Reset
SIRIUS Innovations Thermal overload relay, motor protection 7, 0...10 A, S00, Class 10, independent assembly screw connection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Thermal relays**

Additional Product Information

Technical data

Overload relay 7.0...10 A Thermal For motor protection Size S00, Class 10 Stand-alone installation Main circuit: Screw Auxiliary circuit: Screw Manual-Automatic-Reset

product brand name SIRIUS

product designation thermal overload relay

product type designation 3RU2

General technical data

size of overload relay S00

size of contactor can be combined company-specific S00

power loss [W] for rated value of the current at AC in hot operating state 6.6 W

? per pole 2.2 W

insulation voltage with degree of pollution 3 at AC rated value 690 V

surge voltage resistance rated value 6 kV
maximum permissible voltage for safe isolation in networks with grounded star point
? between auxiliary and auxiliary circuit 440 V
? between auxiliary and auxiliary circuit 440 V
? between main and auxiliary circuit 440 V
? between main and auxiliary circuit 440 V
shock resistance according to IEC 60068-2-27 8g / 11 ms
type of protection according to ATEX directive 2014/34/EU Ex II (2) GD
certificate of suitability according to ATEX directive 2014/34/EU DMT 98 ATEX G 001
reference code according to IEC 81346-2 F
Substance Prohibitance (Date) 10/01/2009
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -40 ... +70 °C
? during storage -55 ... +80 °C
? during transport -55 ... +80 °C
temperature compensation -40 ... +60 °C
relative humidity during operation 10 ... 95 %
Main circuit
number of poles for main current circuit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RU2116-1JB1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.