

INDUSTRIAL COMPONENT DATA

3RV1363-7EN10 SIEMENS Molded case circuit breaker 3RV1 for starter combination Standard switching capacity R..

Brand: SIEMENS | Manufacturer Part Number: 3RV1363-7EN10



Manufacturer	SIEMENS
MPN / Reference	3RV1363-7EN10
Catalog number	13637
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-30A915ABC8
Generated	2026-08-06

Product Overview

Molded case circuit breaker 3RV1 for starter combination Standard switching capacity Rated current $I_n = 250$ A electronic release Short-circuit protection adjustable $1-10 \times I_n$ $I_{cu} = 120$ kA at 400 V 3-pole, Screw terminal including phase barriers INTERRUPT. AUTOM. COMPACT. 3RV1 P/ COMBI. STARTING POWER STANDARD CURRENT RATED $I_n=250$ A ELECTRONIC TRIGGER PROTEC. AGAINST CORTACIRC. DIMMABLE $1-10 \times I_n$ $I_{cu} = 120$ KA BEI 400V 3poles, screw connection PHASE SEPARATORS INCL.. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Motor protection switches

Additional Product Information

Technical data

Molded case circuit breaker 3RV1 for starter combination Standard switching capacity Rated current $I_n = 250$ A electronic release Short-circuit protection adjustable $1-10 \times I_n$ $I_{cu} = 120$ kA at 400 V 3-pole, Screw terminal including phase barriers product brand name SIRIUS

product designation molded-case circuit breaker

design of the product for starter combinations

product type designation 3RV1

General technical data

product extension auxiliary switch Yes

surge voltage resistance rated value 8 000 V

protection class IP on the front IP20

shock resistance 12g / 11 ms
mechanical service life (switching cycles) of the main contacts typical 20 000
continuous current rated value 250 A
Substance Prohibitance (Date) 01/08/2008
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -25 ... +60 °C
? during storage -40 ... +70 °C
? during transport -40 ... +70 °C
Main circuit
number of poles for main current circuit 3
operating voltage
? rated value 690 V
? rated value 20 ... 690 V
? at AC-3 rated value maximum 690 V
operational current at AC-3 at 400 V rated value 250 A
operating power at AC-3
? at 400 V rated value 132 kW
operating frequency at AC-3 maximum 15 1/h
Auxiliary circuit
number of NC contacts for auxiliary contacts 0
number of NO contacts for auxiliary contacts 0
number of CO contacts for auxiliary contacts 0
Protective and monitoring functions
product function
? ground fault detection No
? pha...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RV1363-7EN10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.