

INDUSTRIAL COMPONENT DATA

3RV2042-4KB10 SIEMENS Circuit breaker size S3 for motor protection, Class 20 A-release 57...75 A N-release 9..

Brand: SIEMENS | Manufacturer Part Number: 3RV2042-4KB10



Manufacturer	SIEMENS
MPN / Reference	3RV2042-4KB10
Catalog number	20424
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-D1DE31919B
Generated	2026-08-06

Product Overview

Circuit breaker size S3 for motor protection, Class 20 A-release 57...75 A N-release 975 A screw terminal Increased switching capacity 100 kA

CIRCUIT-BREAKER SIZE S3, FOR MOTOR PROTECTION, CLASS 20, A-REL. 57...75A, N-REL. 975A, SCREW TERMINAL, INCREASED BREAKING CAP. 100KA.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Motor protection switches

Additional Product Information

Technical data

Circuit breaker size S3 for motor protection, Class 20 A-release 57...75 A N-release 975 A screw terminal Increased switching capacity 100 kA

product brand name SIRIUS

product designation Circuit breaker

design of the product For motor protection

product type designation 3RV2

General technical data

size of the circuit-breaker S3

size of contactor can be combined company-specific S3

product extension auxiliary switch Yes

power loss [W] for rated value of the current

? at AC in hot operating state 38 W
? at AC in hot operating state per pole 12.7 W
insulation voltage with degree of pollution 3 at AC rated value 1 000 V
surge voltage resistance rated value 8 kV
maximum permissible voltage for safe isolation in networks with grounded star point
? between main and auxiliary circuit 400 V
? between main and auxiliary circuit 400 V
shock resistance according to IEC 60068-2-27 25g / 11 ms Sinus
mechanical service life (switching cycles)
? of the main contacts typical 25 000
? of auxiliary contacts typical 25 000
electrical endurance (switching cycles) typical 25 000
reference code according to IEC 81346-2 Q
Substance Prohibitance (Date) 03/01/2017
Ambient conditions
installation altitude at height above sea level maximum 2 000 m
ambient temperature
? during operation -20 ... +60 °C
? during storage -50 ... +80 °C
? during transport -50 ... +80 °C
temperature compensation -20 ... +60 °C
relative humidity during operation 10 ... 95 %
Main circuit
number of poles for mai...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RV2042-4KB10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.