

INDUSTRIAL COMPONENT DATA

3RV2321-1BC10 SIEMENS Circuit breaker size S0 for starter combination Rated current 2 A N-release 26 A screw..

Brand: SIEMENS | Manufacturer Part Number: 3RV2321-1BC10



Manufacturer	SIEMENS
MPN / Reference	3RV2321-1BC10
Catalog number	23211
Category	Motor protection circuit-breaker
Minimum order	1 Pcs
Document ID	EO-5DFE46DFF4
Generated	2026-08-04

Product Overview

Circuit breaker size S0 for starter combination Rated current 2 A N-release 26 A screw terminal Standard switching capacity

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Motor protection switches

Additional Product Information

Technical data

Circuit breaker size S0 for starter combination Rated current 2 A N-release 26 A screw terminal Standard switching capacity

product brand name SIRIUS

product designation Circuit breaker

design of the product For starter combinations

product type designation 3RV2

General technical data

size of the circuit-breaker S0

size of contactor can be combined company-specific S00, S0

product extension auxiliary switch Yes

power loss [W] for rated value of the current

? at AC in hot operating state 7.25 W

? at AC in hot operating state per pole 2.4 W

insulation voltage with degree of pollution 3 at AC rated value 690 V

surge voltage resistance rated value 6 kV

maximum permissible voltage for safe isolation in networks with grounded star point

? between main and auxiliary circuit 400 V

? between main and auxiliary circuit 400 V

shock resistance according to IEC 60068-2-27 25g / 11 ms

mechanical service life (switching cycles)

? of the main contacts typical 100 000

? of auxiliary contacts typical 100 000

electrical endurance (switching cycles) typical 100 000

reference code according to IEC 81346-2 Q

Substance Prohibitance (Date) 10/01/2009

Ambient conditions

installation altitude at height above sea level maximum 2 000 m

ambient temperature

? during operation -20 ... +60 °C

? during storage -50 ... +80 °C

? during transport -50 ... +80 °C

relative humidity during operation 10 ... 95 %

Main circuit

number of poles for main current circuit 3

operating voltage

? rated value 6...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RV2321-1BC10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.