

**INDUSTRIAL COMPONENT DATA**

# 3RV2331-4BC10 SIEMENS Circuit breaker size S2 for starter combination Rated current 20 A N-release 260 A scr..

Brand: SIEMENS | Manufacturer Part Number: 3RV2331-4BC10



|                 |                                  |
|-----------------|----------------------------------|
| Manufacturer    | SIEMENS                          |
| MPN / Reference | 3RV2331-4BC10                    |
| Catalog number  | 23314                            |
| Category        | Motor protection circuit-breaker |
| Minimum order   | 1 Pcs                            |
| Document ID     | EO-4FB92DABCC                    |
| Generated       | 2026-08-05                       |

## Product Overview

Circuit breaker size S2 for starter combination Rated current 20 A N-release 260 A screw terminal Standard switching capacity

MOTOR GUARD, SIZE S2, FOR STARTING COMBINATION, I NOMINAL 20A, I INST. 260A, 65KA, SCREW TERMINALS

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Motor protection switches**

## Additional Product Information

**Technical data**

Circuit breaker size S2 for starter combination Rated current 20 A N-release 260 A screw terminal Standard switching capacity

product brand name SIRIUS

product designation Circuit breaker

design of the product For starter combinations

product type designation 3RV2

General technical data

size of the circuit-breaker S2

size of contactor can be combined company-specific S2

product extension auxiliary switch Yes

power loss [W] for rated value of the current

? at AC in hot operating state 14.5 W

? at AC in hot operating state per pole 4.8 W  
insulation voltage with degree of pollution 3 at AC rated value 690 V  
surge voltage resistance rated value 6 kV  
maximum permissible voltage for safe isolation in networks with grounded star point  
? between main and auxiliary circuit 400 V  
? between main and auxiliary circuit 400 V  
shock resistance according to IEC 60068-2-27 25g / 11 ms Sinus  
mechanical service life (switching cycles)  
? of the main contacts typical 50 000  
? of auxiliary contacts typical 50 000  
electrical endurance (switching cycles) typical 50 000  
reference code according to IEC 81346-2 Q  
Substance Prohibitance (Date) 10/15/2014  
Ambient conditions  
installation altitude at height above sea level maximum 2 000 m  
ambient temperature  
? during operation -20 ... +60 °C  
? during storage -50 ... +80 °C  
? during transport -50 ... +80 °C  
relative humidity during operation 10 ... 95 %  
Main circuit  
number of poles for main current circuit 3  
operating voltage  
? rated value 6...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RV2331-4BC10 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.