

INDUSTRIAL COMPONENT DATA

3RV2901-1J SIEMENS Auxiliary switch can be mounted on the side 2 NO+2 NC screw terminal for circuit breaker ..

Brand: SIEMENS | Manufacturer Part Number: 3RV2901-1J



Manufacturer	SIEMENS
MPN / Reference	3RV2901-1J
Catalog number	29011
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-BA7970744B
Generated	2026-08-04

Product Overview

Auxiliary switch can be mounted on the side 2 NO+2 NC screw terminal for circuit breaker 3RV2 SIRIUS Innovations 2NA side, screw connection, S00/S0 switches.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Motor protection switches**

Additional Product Information

Technical data

Auxiliary switch can be mounted on the side 2 NO+2 NC screw terminal for circuit breaker 3RV2

General technical data

product brand name SIRIUS

product designation auxiliary switch, lateral

design of the product lateral auxiliary switches

size of the circuit-breaker S00, S0, S2, S3

protection class IP on the front according to IEC 60529 IP20

touch protection on the front according to IEC 60529 finger-safe, for vertical contact from the front

ambient temperature

? during storage °C -50 ... +80

? during operation °C -20 ... +60

Auxiliary circuit

number of NC contacts for auxiliary contacts instantaneous contact 2

number of NO contacts for auxiliary contacts instantaneous contact 2

number of CO contacts of auxiliary contacts instantaneous contact 0

operational current

? of auxiliary contacts

- at AC-12

- at 24 V A 10

- at 230 V A 10

- at 400 V A 10

- at 690 V A 10

- maximum A 10

- at AC-15

- at 24 V A 6

- at 230 V A 4

- at 400 V A 3

- at DC-13

- at 24 V A 2

- at 110 V A 0.5

- at 220 V A 0.25

- at 250 V A 0.25

? at AC-15 at 690 V rated value A 1

Installation/ mounting/ dimensions

fastening method plug-in fixing

width mm 18

height mm 90

depth mm 68

Connections/ Terminals

type of electrical connection for auxiliary and control circuit screw-type terminals

type of connectable conductor cross-sections

? for auxiliary contacts

- solid 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)

- finely stranded

- with core end processing 2x (0.5 ... 1.5 mm²), 2x (0.75 ... 2.5 mm²)

? at...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RV2901-1J with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.