

INDUSTRIAL COMPONENT DATA

3RV2901-2F SIEMENS Auxiliary switch transverse 2 NO spring-type terminal for circuit breaker 3RV2

Brand: SIEMENS | Manufacturer Part Number: 3RV2901-2F



Manufacturer	SIEMENS
MPN / Reference	3RV2901-2F
Catalog number	29012
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-39683B7A85
Generated	2026-08-01

Product Overview

Auxiliary switch transverse 2 NO spring-type terminal for circuit breaker 3RV2
SIRIUS Innovations 2NA transverse, spring connection, S00/S0 switches.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Motor protection switches

Additional Product Information

Technical data

Auxiliary switch transverse 2 NO spring-type terminal for circuit breaker 3RV2

General technical data

product brand name SIRIUS

product designation auxiliary switch, transverse on the front

design of the product transverse auxiliary switches

size of the circuit-breaker S00, S0, S2, S3

protection class IP on the front according to IEC 60529 IP20

touch protection on the front according to IEC 60529 finger-safe, for vertical contact from the front

ambient temperature

? during storage °C -50 ... +80

? during operation °C -20 ... +60

Auxiliary circuit

number of NC contacts for auxiliary contacts instantaneous contact 0

number of NO contacts for auxiliary contacts instantaneous contact 2

number of CO contacts of auxiliary contacts instantaneous contact 0

operational current

? of auxiliary contacts

- at AC-12
- at 24 V A 2.5
- at 230 V A 2.5
- maximum A 2.5
- at AC-15
- at 24 V A 2
- at 230 V A 0.5
- at DC-13
- at 24 V A 1
- at 48 V A 0.3
- at 60 V A 0.15

Installation/ mounting/ dimensions

fastening method plug-in fixing

width mm 45

height mm 13

depth mm 17

Connections/ Terminals

type of electrical connection for auxiliary and control circuit spring-loaded terminals

type of connectable conductor cross-sections

? for auxiliary contacts

- solid 2x (0.5 ... 2.5 mm²)
- finely stranded
- with core end processing 2x (0.5 ... 1.5 mm²)
- without core end processing 2x (0.5 ... 1.5 mm²)
- ? at AWG cables for auxiliary contacts 2x (20 ... 14)

Certificates/ approvals

certificate....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RV2901-2F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.