

INDUSTRIAL COMPONENT DATA

3RV2902-4DP0 SIEMENS Shunt release 210-240 V AC, 50/60 Hz, 100% ON period 190-330 V AC, 50/60 Hz, 5 s ON per..

Brand: SIEMENS | Manufacturer Part Number: 3RV2902-4DP0



Manufacturer	SIEMENS
MPN / Reference	3RV2902-4DP0
Catalog number	29024
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-6DCDFE46E2
Generated	2026-08-05

Product Overview

Shunt release 210-240 V AC, 50/60 Hz, 100% ON period 190-330 V AC, 50/60 Hz, 5 s ON period 190-330 V AC, 5 s ON period with ring cable lug connection for circuit breaker 3RV2

SIRIUS Innovations Shutter Release, AC 210...240V, 50/60HZ, 100% ED, AC 190...330V, 50/60HZ, 5SEC ED, DC 190...330V, 5SEC ED, Ring Connection, S00/S0 Switches

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Motor protection switches

Additional Product Information

Technical data

Shunt release 210-240 V AC, 50/60 Hz, 100% ON period 190-330 V AC, 50/60 Hz, 5 s ON period 190-330 V AC, 5 s ON period with ring cable lug connection for circuit breaker 3RV2

General technical data

product brand name SIRIUS

product designation shunt release

size of the circuit-breaker S00, S0, S2, S3

suitability for use motor circuit breaker

protection class IP on the front according to IEC 60529 IP00

touch protection on the front according to IEC 60529 finger-safe, for vertical contact from the front

design of short-circuit protection fuse

degree of pollution 3

insulation voltage rated value 690 V
insulation voltage with degree of pollution 3 at AC rated value 690 V
ambient temperature
? during storage -50 ... +80 °C
? during operation -20 ... +60 °C
reference code according to EN 61346-2 F
Auxiliary circuit
number of NC contacts for auxiliary contacts instantaneous contact 0
number of NO contacts for auxiliary contacts instantaneous contact 0
number of NO contacts for auxiliary contacts leading contact 0
number of CO contacts of auxiliary contacts instantaneous contact 0
Control circuit/ Control
type of voltage of the control supply voltage AC
control supply voltage frequency
? 1
- initial rated value 50 Hz
- final rated value 60 Hz
control supply voltage
? 1
- at AC
- at 50 Hz initial rated value 210 V
- at 50 Hz final rated value 240 V
- at 60 Hz final rated value 240 V
- at 60 Hz initial rated value 210 V
Installation/ mounting/ dimensions
fastening metho...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RV2902-4DP0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.