

**INDUSTRIAL COMPONENT DATA**

# 3RV2917-5D SIEMENS Terminal block 6 mm<sup>2</sup> for current outfeed and also for connection of 3-phase busbars

Brand: SIEMENS | Manufacturer Part Number: 3RV2917-5D



|                 |                                                           |
|-----------------|-----------------------------------------------------------|
| Manufacturer    | SIEMENS                                                   |
| MPN / Reference | 3RV2917-5D                                                |
| Catalog number  | 29175                                                     |
| Category        | Accessories/spare parts for low-voltage switch technology |
| Minimum order   | 1 Pcs                                                     |
| Document ID     | EO-40B8540CE4                                             |
| Generated       | 2026-08-04                                                |

## Product Overview

Terminal block 6 mm<sup>2</sup> for current outfeed and also for connection of 3-phase busbars

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Motor protection switches**

## Additional Product Information

**Technical data**

Terminal block 6 mm<sup>2</sup> for current outfeed and also for connection of 3-phase busbars

**General technical data**

product brand name SIRIUS

product designation Terminal block

design of the product for power outlet

protection class IP on the front according to IEC 60529 IP20

touch protection on the front according to IEC 60529 finger-safe, for vertical contact from the front

insulation voltage with degree of pollution 3 at AC rated value V 500

ambient temperature

? during storage °C -50 ... +80

? during operation °C -20 ... +60

ampacity maximum A 32

Installation/ mounting/ dimensions

width mm 40.4

height mm 34.5

depth mm 50

Connections/ Terminals

type of electrical connection for main current circuit spring-loaded terminals

type of connectable conductor cross-sections

? for main contacts

- solid 1x (1.5 ... 6 mm<sup>2</sup>)

- stranded 1x (1.5 ... 6 mm<sup>2</sup>)

- finely stranded

- with core end processing 1x (1.5 ... 4 mm<sup>2</sup>)

- without core end processing 1x (1.5 ... 6 mm<sup>2</sup>)

? at AWG cables for main contacts 1x (15 ... 10)

Certificates/ approvals

certificate of suitability CE / UL / CSA / CCC

Downloads and manuals

General Product Approval Declaration of Conformity

Confirmation

UK Declaration of Conformity

Test Certificates Marine / Shipping

Type Test Certificates/Test Report

Special Test Certificate

Marine / Shipping other

Confirmation

Environmental Confirmations

Railway

Vibration and Shock

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<https://www.siemens.com/...>

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RV2917-5D with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.