

## INDUSTRIAL COMPONENT DATA

# 3RV2926-2B SIEMENS Door-coupling rotary operating mechanism for circuit breaker Size S00/S0 Handle gray new ..

Brand: SIEMENS | Manufacturer Part Number: 3RV2926-2B



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | SIEMENS                             |
| MPN / Reference | 3RV2926-2B                          |
| Catalog number  | 29262                               |
| Category        | Door coupling handle for switchgear |
| Minimum order   | 1 Pcs                               |
| Document ID     | EO-5774331E0D                       |
| Generated       | 2026-08-03                          |

## Product Overview

door-coupling rotary operating mechanism for circuit breaker size S00/S0 handle gray new design !!! phased-out product !!!  
replacement type is 3RV2926-3B  
SIRIUS Innovations SIRIUS circuit breaker, door-coupling rotary operating mechanism for circuit-breakers size S0, handle gray new design

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                              |
|--------------|--------------------------------------------------------------|
| Catalog path | SIEMENS > CONTROL AND CONTACTORS > Motor protection switches |
|--------------|--------------------------------------------------------------|

## Additional Product Information

## Technical data

door-coupling rotary operating mechanism for circuit breaker size S00/S0 handle gray new design !!! phased-out product !!!  
replacement type is 3RV2926-3B

## General technical data

product brand name SIRIUS

product designation door-coupling rotary operating mechanism for heavy-duty operating conditions

size of the circuit-breaker S0

design of the product standard

suitability for use circuit-breakers S0

ambient temperature

? during storage °C -50 ... +80

? during operation °C -20 ... +70

operating frequency maximum 1/h 15

color of the actuating element gray

Installation/ mounting/ dimensions

mounting position any

fastening method screw fixing

width mm 75

height mm 75

depth mm 78

length mm 300

diameter mm 40

required spacing for grounded parts

? forwards mm 0

? backwards mm 0

? upwards mm 0

? at the side mm 0

? downwards mm 0

Certificates/ approvals

certificate of suitability CE / UL / CSA

Downloads and manuals

General Product Approval Test Certificates Marine / Shipping

Confirmation

Type Test Certificates/Test Report

Marine / Shipping other

Confirmation

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RV2926-2B>

Cax online generator<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RV2926-2B>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)<https://support.industry.siemens.com>

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RV2926-2B with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.