

INDUSTRIAL COMPONENT DATA

3RW3016-1BB14 SIEMENS SIRIUS soft starter S00 9 A, 4 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC Screw ter..

Brand: SIEMENS | Manufacturer Part Number: 3RW3016-1BB14



Manufacturer	SIEMENS
MPN / Reference	3RW3016-1BB14
Catalog number	30161
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-41855F5CB8
Generated	2026-08-06

Product Overview

SIRIUS soft starter S00 9 A, 4 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC Screw terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > SIRIUS soft starter

Additional Product Information

Technical data

SIRIUS soft starter S00 9 A, 4 kW/400 V, 40 °C 200-480 V AC, 110-230 V AC/DC Screw terminals

General technical data

product brand name SIRIUS

product feature

? integrated bypass contact system Yes

? thyristors Yes

product function

? intrinsic device protection No

? motor overload protection No

? evaluation of thermistor motor protection No

? external reset No

? adjustable current limitation No

? inside-delta circuit No

product component motor brake output No

insulation voltage rated value V 600

degree of pollution 3, acc. to IEC 60947-4-2

reference code according to EN 61346-2 Q

reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750 G

Power Electronics

product designation Soft starter

operational current

? at 40 °C rated value A 9

? at 50 °C rated value A 8

? at 60 °C rated value A 7

yielded mechanical performance for 3-phase motors

? at 230 V

- at standard circuit at 40 °C rated value kW 2.2

? at 400 V

- at standard circuit at 40 °C rated value kW 4

yielded mechanical performance [hp] for 3-phase AC motor at 200/208 V at standard circuit at 50 °C rated value hp 2

operating frequency rated value Hz 50 ... 60

relative negative tolerance of the operating frequency % -10

relative positive tolerance of the operating frequency % 10

operating voltage at standard circuit rated value V 200 ... 480

relative negative tolerance of the operating voltage at standard circuit % -15

relative positive tolerance of the operating voltage at st...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RW3016-1BB14 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.