

INDUSTRIAL COMPONENT DATA

3RW4026-1TB04 SIEMENS SIRIUS soft starter S0 25 A, 11 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC Screw termina..

Brand: SIEMENS | Manufacturer Part Number: 3RW4026-1TB04



Manufacturer	SIEMENS
MPN / Reference	3RW4026-1TB04
Catalog number	40261
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-87D0A38041
Generated	2026-08-06

Product Overview

SIRIUS soft starter S0 25 A, 11 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC Screw terminals Thermistor motor protection
SIRIUS Electronic starter, soft start and stop, S0 motor protection 200-480 V AC/400V, 40°C, CLASS10: 25A, 11KW;
Vm:24V AC/DC, screw connection, thermistor protection.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > SIRIUS soft starter
--------------	--

Additional Product Information

Technical data

SIRIUS soft starter S0 25 A, 11 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC Screw terminals Thermistor motor protection

General technical data

product brand name SIRIUS

product feature

? integrated bypass contact system Yes

? thyristors Yes

product function

? intrinsic device protection Yes

? motor overload protection Yes

? evaluation of thermistor motor protection Yes

? external reset Yes

? adjustable current limitation Yes

? inside-delta circuit No
product component motor brake output No
insulation voltage rated value V 600
degree of pollution 3, acc. to IEC 60947-4-2
reference code according to EN 61346-2 Q
reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750 G
Power Electronics
product designation Soft starter
operational current
? at 40 °C rated value A 25
? at 50 °C rated value A 23
? at 60 °C rated value A 21
yielded mechanical performance for 3-phase motors
? at 230 V
- at standard circuit at 40 °C rated value kW 5.5
? at 400 V
- at standard circuit at 40 °C rated value kW 11
yielded mechanical performance [hp] for 3-phase AC motor at 200/208 V at standard circuit at 50 °C rated value hp 5
operating frequency rated value Hz 50 ... 60
relative negative tolerance of the operating frequency % -10
relative positive tolerance of the operating frequency % 10
operating voltage at standard circuit rated value V 200 ... 480
relative negative tolerance of the operating voltage at standard circuit % -15
relative positive toleran...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RW4026-1TB04 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.