

INDUSTRIAL COMPONENT DATA

3RW4037-2BB05 SIEMENS SIRIUS soft starter S2 63 A, 37 kW/500 V, 40 °C 400-600 V AC, 24 V AC/DC spring-type t..

Brand: SIEMENS | Manufacturer Part Number: 3RW4037-2BB05



Manufacturer	SIEMENS
MPN / Reference	3RW4037-2BB05
Catalog number	40372
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-F1CC803E49
Generated	2026-08-06

Product Overview

SIRIUS soft starter S2 63 A, 37 kW/500 V, 40 °C 400-600 V AC, 24 V AC/DC spring-type terminals

SIRIUS Electronic starter,smooth start and stop,motor protection S2 400-600 V AC/500V, 40°C, CLASS10 : 63A, 37KW ; Vm:24V AC/DC, spring connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > SIRIUS soft starter**

Additional Product Information

Technical data

SIRIUS soft starter S2 63 A, 37 kW/500 V, 40 °C 400-600 V AC, 24 V AC/DC spring-type terminals

General technical data

product brand name SIRIUS

product feature

? integrated bypass contact system Yes

? thyristors Yes

product function

? intrinsic device protection Yes

? motor overload protection Yes

? evaluation of thermistor motor protection No

? external reset Yes

? adjustable current limitation Yes

? inside-delta circuit No
product component motor brake output No
insulation voltage rated value V 600
degree of pollution 3, acc. to IEC 60947-4-2
reference code according to EN 61346-2 Q
reference code according to DIN 40719 extended according to IEC 204-2 according to IEC 750 G
Power Electronics
product designation Soft starter
operational current
? at 40 °C rated value A 63
? at 50 °C rated value A 58
? at 60 °C rated value A 53
yielded mechanical performance for 3-phase motors
? at 400 V
- at standard circuit at 40 °C rated value kW 30
? at 500 V
- at standard circuit at 40 °C rated value kW 37
operating frequency rated value Hz 50 ... 60
relative negative tolerance of the operating frequency % -10
relative positive tolerance of the operating frequency % 10
operating voltage at standard circuit rated value V 400 ... 600
relative negative tolerance of the operating voltage at standard circuit % -15
relative positive tolerance of the operating voltage at standard circuit % 10
minimum load [%] % 20
adjustable motor current for motor overload protection minimum ra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RW4037-2BB05 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.