

INDUSTRIAL COMPONENT DATA

3RW4436-2BC46 SIEMENS SIRIUS soft starter Values at 690 V, 40 °C standard: 162 A, 160 kW Inside-delta: only ..

Brand: SIEMENS | Manufacturer Part Number: 3RW4436-2BC46



Manufacturer	SIEMENS
MPN / Reference	3RW4436-2BC46
Catalog number	44362
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-7ED64DE85F
Generated	2026-08-04

Product Overview

SIRIUS soft starter Values at 690 V, 40 °C standard: 162 A, 160 kW Inside-delta: only up to 600 V 400-690 V AC, 230 V AC spring-type terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5536-2HA16<

SIRIUS High performance electronic starter 400 - 690 V AC/690 V, 40°C, CLASS10 : (c. standard: 162A, 160KW) Vm:230V AC, spring connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Soft starters for high-feature applications**

Additional Product Information

Technical data

SIRIUS soft starter Values at 690 V, 40 °C standard: 162 A, 160 kW Inside-delta: only up to 600 V 400-690 V AC, 230 V AC spring-type terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5536-2HA16

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RW4436-2BC46 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.