

INDUSTRIAL COMPONENT DATA

3RW4446-2BC34 SIEMENS SIRIUS soft starter Values at 460 V, 50 °C standard: 315 A, 250 hp Inside-delta: 546 A..

Brand: SIEMENS | Manufacturer Part Number: 3RW4446-2BC34



Manufacturer	SIEMENS
MPN / Reference	3RW4446-2BC34
Catalog number	44462
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-307185C697
Generated	2026-08-04

Product Overview

SIRIUS soft starter Values at 460 V, 50 °C standard: 315 A, 250 hp Inside-delta: 546 A, 450 hp 200-460 V AC, 115 V AC spring-type terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5546-2HA14<

SIRIUS High performance electronic starter 200 - 460 V AC/400 V, 40°C, CLASS10 : (c. standard: 356A, 200KW, c. root 3: 617A, 355KW) Vm: 115V AC, spring connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Soft starters for high-feature applications

Additional Product Information

Technical data

SIRIUS soft starter Values at 460 V, 50 °C standard: 315 A, 250 hp Inside-delta: 546 A, 450 hp 200-460 V AC, 115 V AC spring-type terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5546-2HA14

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RW4446-2BC34 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.