

INDUSTRIAL COMPONENT DATA

3RW4456-6BC34 SIEMENS SIRIUS soft starter Values at 460 V, 50 °C standard: 693 A, 600 hp Inside-delta: 1200 ..

Brand: SIEMENS | Manufacturer Part Number: 3RW4456-6BC34



Manufacturer	SIEMENS
MPN / Reference	3RW4456-6BC34
Catalog number	44566
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-4B1D0D8E4A
Generated	2026-08-06

Product Overview

SIRIUS soft starter Values at 460 V, 50 °C standard: 693 A, 600 hp Inside-delta: 1200 A, 1050 hp 200-460 V AC, 115 V AC Screw terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5554-6HA14< SIRIUS High performance electronic starter 200 - 460 V AC/400 V, 40°C, CLASS10 : (c. standard: 780A, 450KW, c. root 3: 1351A, 800KW) Vm: 115V AC, screw connection

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Soft starters for high-feature applications**

Additional Product Information

Additional data

Product

Article Number (Market Facing Number) 3RW4456-6BC34

Product Description SIRIUS soft starter Values at 460 V, 50 °C standard: 693 A, 600 hp Inside-delta: 1200 A, 1050 hp 200-460 V AC, 115 V AC Screw terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5554-6HA14>3RW5554-6HA14

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RW4456-6BC34 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.