

INDUSTRIAL COMPONENT DATA

3RW4465-6BC45 SIEMENS SIRIUS soft starter Values at 500 V, 40 °C standard: 1076 A, 800 kW Inside-delta: 1864..

Brand: SIEMENS | Manufacturer Part Number: 3RW4465-6BC45



Manufacturer	SIEMENS
MPN / Reference	3RW4465-6BC45
Catalog number	44656
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-5609B3AF0D
Generated	2026-08-03

Product Overview

SIRIUS soft starter Values at 500 V, 40 °C standard: 1076 A, 800 kW Inside-delta: 1864 A, 1350 kW 400-600 V AC, 230 V AC Screw terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5558-6HA16<

SIRIUS High performance electronic starter 400 - 600 V AC/500 V, 40°C, CLASS10 : (c. standard: 1076A, 800KW, c. root 3: 1864A, 1350KW) Vm: 230V AC, screw connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Soft starters for high-feature applications**

Additional Product Information

Technical data

SIRIUS soft starter Values at 500 V, 40 °C standard: 1076 A, 800 kW Inside-delta: 1864 A, 1350 kW 400-600 V AC, 230 V AC Screw terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5558-6HA16

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RW4465-6BC45 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.