

INDUSTRIAL COMPONENT DATA

3RW4466-6BC34 SIEMENS SIRIUS soft starter Values at 460 V, 50 °C standard: 1076 A, 950 hp Inside-delta: 1864..

Brand: SIEMENS | Manufacturer Part Number: 3RW4466-6BC34



Manufacturer	SIEMENS
MPN / Reference	3RW4466-6BC34
Catalog number	44666
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-9163CCF539
Generated	2026-08-04

Product Overview

SIRIUS soft starter Values at 460 V, 50 °C standard: 1076 A, 950 hp Inside-delta: 1864 A, 1700 hp 200-460 V AC, 115 V AC Screw terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5558-6HA14<

SIRIUS High performance electronic starter 200 - 460 V AC/400 V, 40°C, CLASS10 : (c. standard: 1214A, 710KW, c. root 3: 2103A, 1200KW) Vm: 115V AC, screw connection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Soft starters for high-feature applications
--------------	--

Additional Product Information

Technical data

SIRIUS soft starter Values at 460 V, 50 °C standard: 1076 A, 950 hp Inside-delta: 1864 A, 1700 hp 200-460 V AC, 115 V AC Screw terminals !!! Phased-out product !!! Successor is SIRIUS 3RW5, Preferred successor type is >>3RW5558-6HA14

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RW4466-6BC34 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.