

INDUSTRIAL COMPONENT DATA

3RW5215-1TC15 SIEMENS SIRIUS soft starter 200-600 V 25 A, 110-250 V AC Screw terminals Thermistor input

Brand: SIEMENS | Manufacturer Part Number: 3RW5215-1TC15



Manufacturer	SIEMENS
MPN / Reference	3RW5215-1TC15
Catalog number	10000
Category	Soft starter
Minimum order	1 Pcs
Document ID	EO-BAEED1884D
Generated	2026-08-03

Product Overview

SIRIUS soft starter 200-600 V 25 A, 110-250 V AC Screw terminals Thermistor input
SIRIUS soft starter 200-600 V 25 A, 110-250 V AC Screw connection Thermistor input.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Soft starters for high-feature applications

Additional Product Information

Technical data

SIRIUS soft starter 200-600 V 25 A, 110-250 V AC Screw terminals Thermistor input

product brand name SIRIUS

product category Hybrid switching devices

product designation Soft starter

product type designation 3RW52

manufacturer's article number

? of standard HMI module usable 3RW5980-0HS00

? of high feature HMI module usable 3RW5980-0HF00

? of communication module PROFINET standard usable 3RW5980-0CS00

? of communication module PROFIBUS usable 3RW5980-0CP00

? of communication module Modbus TCP usable 3RW5980-0CT00

? of communication module Modbus RTU usable 3RW5980-0CR00

? of communication module Ethernet/IP 3RW5980-0CE00

? of circuit breaker usable at 400 V 3RV2032-4EA10; Type of coordination 1, I_q = 65 kA, CLASS 10
? of circuit breaker usable at 500 V 3RV2032-4EA10; Type of coordination 1, I_q = 15 kA, CLASS 10
? of circuit breaker usable at 400 V at inside-delta circuit 3RV2032-4VA10; Type of coordination 1, I_q = 65 kA, CLASS 10
? of circuit breaker usable at 500 V at inside-delta circuit 3RV2032-4VA10; Type of coordination 1, I_q = 15 kA, CLASS 10
? of the gG fuse usable up to 690 V 3NA3822-6; Type of coordination 1, I_q = 65 kA
? of the gG fuse usable at inside-delta circuit up to 500 V 3NA3822-6; Type of coordination 1, I_q = 65 kA
? of full range R fuse link for semiconductor protection usable up to 690 V 3NE1817-0; Type of coordination 2, I_q = 65 kA
? of back-up R fuse link for semiconductor protection usable up to 690 V 3NE8021-1; Type of coordination 2, I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RW5215-1TC15 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.