

## INDUSTRIAL COMPONENT DATA

# 3RW5515-1HA14 SIEMENS SIRIUS soft starter 200-480 V 25 A, 110-250 V AC Screw terminals

Brand: SIEMENS | Manufacturer Part Number: 3RW5515-1HA14



|                 |               |
|-----------------|---------------|
| Manufacturer    | SIEMENS       |
| MPN / Reference | 3RW5515-1HA14 |
| Catalog number  | 10000         |
| Category        | Soft starter  |
| Minimum order   | 1 Pcs         |
| Document ID     | EO-AE0E716924 |
| Generated       | 2026-08-05    |

## Product Overview

SIRIUS soft starter 200-480 V 25 A, 110-250 V AC Screw terminals

SIRIUS soft starter 200-480 V 25 A, 110-250 V AC Screw connection

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS &gt; CONTROL AND CONTACTORS &gt; Soft starters for high-feature applications

## Additional Product Information

Technical data

SIRIUS soft starter 200-480 V 25 A, 110-250 V AC Screw terminals

product brand name SIRIUS

product category Hybrid switching devices

product designation Soft starter

product type designation 3RW55

manufacturer's article number

? of high feature HMI module usable 3RW5980-0HF00

? of communication module PROFINET standard usable 3RW5980-0CS00

? of communication module PROFINET high-feature usable 3RW5950-0CH00

? of communication module PROFIBUS usable 3RW5980-0CP00

? of communication module Modbus TCP usable 3RW5980-0CT00

? of communication module Modbus RTU usable 3RW5980-0CR00

? of communication module Ethernet/IP 3RW5980-0CE00

? of circuit breaker usable at 400 V 3RV2032-4EA10; Type of coordination 1, Iq = 65 kA, CLASS 10  
? of circuit breaker usable at 500 V 3RV2032-4EA10; Type of coordination 1, Iq = 15 kA, CLASS 10  
? of circuit breaker usable at 400 V at inside-delta circuit 3RV2032-4VA10; Type of coordination 1, Iq = 65 kA, CLASS 10  
? of circuit breaker usable at 500 V at inside-delta circuit 3RV2032-4VA10; Type of coordination 1, Iq = 15 kA, CLASS 10  
? of the gG fuse usable up to 690 V 3NA3822-6; Type of coordination 1, Iq = 65 kA  
? of the gG fuse usable at inside-delta circuit up to 500 V 3NA3822-6; Type of coordination 1, Iq = 65 kA  
? of full range R fuse link for semiconductor protection usable up to 690 V 3NE1817-0; Type of coordination 2, Iq = 65 kA  
? of back-up R fuse link for semiconductor protection usable up to 690 V 3NE8021-1; Type of coordinatio...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3RW5515-1HA14 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.