

INDUSTRIAL COMPONENT DATA

3SB2000-4PB01 SIEMENS Key-operated switch, 16 mm, round, plastic, CES, SB2, 3 switch positions I-O-II, latch..

Brand: SIEMENS | Manufacturer Part Number: 3SB2000-4PB01



Manufacturer	SIEMENS
MPN / Reference	3SB2000-4PB01
Catalog number	20004
Category	Front element for selector switch
Minimum order	1 Pcs
Document ID	EO-D15C02745C
Generated	2026-08-04

Product Overview

Key-operated switch, 16 mm, round, plastic, CES, SB2, 3 switch positions I-O-II, latching, Actuating angle 2 x 62 degree
Key removal I+O+II, possible special locks: SB3, SB4, SB5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Key-operated switch, 16 mm, round, plastic, CES, SB2, 3 switch positions I-O-II, latching, Actuating angle 2 x 62 degree
Key removal I+O+II, possible special locks: SB3, SB4, SB5

product brand name SIRIUS

product designation Key-operated switches

design of the product Single device round

product type designation 3SB2

Enclosure

number of command points 1

Actuator

design of the actuating element Key-operated switch

principle of operation of the actuating element latching

product extension optional light source No

material of the actuating element plastic

outer diameter of the actuating element 19 mm
type of unlocking device key unlatching
number of switching positions 3
switch position for key distraction I+O+II
actuating angle
? clockwise 62°
? anticlockwise 62°
lock make CES
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
Holder
material of the holder Plastic
General technical data
product function
? EMERGENCY OFF function No
? EMERGENCY STOP function No
protection class IP IP65
vibration resistance according to IEC 60068-2-6 20 ... 200 Hz: 5g
operating frequency maximum 1 000 1/h
mechanical service life (switching cycles) typical 300 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 07/01/2006
Connections/ Terminals
tightening torque of the screws in the bracket 0.4 N·m
Ambient conditions
ambient temperature
? during operation -25 ... +70 °...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SB2000-4PB01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.