

INDUSTRIAL COMPONENT DATA

3SB2001-0AF01 SIEMENS Illuminated pushbutton, 16 mm, round, plastic, blue, pushbutton, flat

Brand: SIEMENS | Manufacturer Part Number: 3SB2001-0AF01



Manufacturer	SIEMENS
MPN / Reference	3SB2001-0AF01
Catalog number	20010
Category	Front element for push button
Minimum order	1 Pcs
Document ID	EO-DF2CA22BBC
Generated	2026-08-03

Product Overview

Illuminated pushbutton, 16 mm, round, plastic, blue, pushbutton, flat

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Illuminated pushbutton, 16 mm, round, plastic, blue, pushbutton, flat

product brand name SIRIUS

product designation Illuminated pushbuttons

design of the product Single device round

product type designation 3SB2

Enclosure

number of command points 1

Actuator

design of the actuating element Illuminated pushbutton

principle of operation of the actuating element momentary contact type

product extension optional light source Yes

color of the actuating element blue

material of the actuating element plastic

shape of the actuating element Flat pushbutton

outer diameter of the actuating element 19 mm
type of unlocking device without
number of switching positions 2
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
Holder
material of the holder Plastic
General technical data
product function
? EMERGENCY OFF function No
? EMERGENCY STOP function No
protection class IP IP65
vibration resistance according to IEC 60068-2-6 20 ... 200 Hz: 5g
operating frequency maximum 1 000 1/h
mechanical service life (switching cycles) typical 3 000 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 07/01/2006
Connections/ Terminals
tightening torque of the screws in the bracket 0.4 N·m
Ambient conditions
ambient temperature
? during operation -25 ... +70 °C
? during storage -40 ... +80 °C
environmental category during operation according to IEC 60721 3K6
Installation/ mount...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SB2001-0AF01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.