

INDUSTRIAL COMPONENT DATA

3SB2203-1AC01 SIEMENS Emergency stop mushroom pushbutton, 16 mm, round, plastic, red, latching, with rotate-..

Brand: SIEMENS | Manufacturer Part Number: 3SB2203-1AC01



Manufacturer	SIEMENS
MPN / Reference	3SB2203-1AC01
Catalog number	22031
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-EFF3483320
Generated	2026-08-05

Product Overview

Emergency stop mushroom pushbutton, 16 mm, round, plastic, red, latching, with rotate-to-unlatch mechanism, according to ISO 13850, 1 NC, with yellow backing plate, EMERGENCY STOP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data

Emergency stop mushroom pushbutton, 16 mm, round, plastic, red, latching, with rotate-to-unlatch mechanism, according to ISO 13850, 1 NC, with yellow backing plate, EMERGENCY STOP

product brand name SIRIUS

product designation EMERGENCY STOP mushroom pushbuttons

design of the product Complete unit round with positive latching in accordance with ISO 13850

product type designation 3SB2

Enclosure

number of command points 1

Actuator

design of the actuating element EMERGENCY STOP mushroom pushbutton

principle of operation of the actuating element latching

product extension optional light source No

color of the actuating element red

material of the actuating element plastic
type of unlocking device rotate-to-unlatch mechanism
number of switching positions 2
Front ring
product component front ring No
Holder
material of the holder Plastic
Contact block/ lampholder
number of lampholders 0
number of switching elements 1
General technical data
product function
? positive opening Yes
? EMERGENCY STOP function Yes
type of voltage of the operating voltage AC/DC
protection class IP IP65
vibration resistance according to IEC 60068-2-6 20 ... 200 Hz: 5g
operating frequency maximum 1 000 1/h
mechanical service life (switching cycles) typical 10 000 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 07/01/2006
operating voltage rated value 5 ... 250 V
Auxiliary circuit
number of NC contacts for auxiliary contacts 1
number of NO contacts for auxiliary cont...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SB2203-1AC01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.