

INDUSTRIAL COMPONENT DATA

3SB2206-0AF01 SIEMENS Illuminated pushbutton, 16 mm, round, plastic, blue, pushbutton, flat, 1 NO, Lampholde..

Brand: SIEMENS | Manufacturer Part Number: 3SB2206-0AF01



Manufacturer	SIEMENS
MPN / Reference	3SB2206-0AF01
Catalog number	22060
Category	Push button, complete
Minimum order	1 Pcs
Document ID	EO-8424CD1A6B
Generated	2026-08-01

Product Overview

Illuminated pushbutton, 16 mm, round, plastic, blue, pushbutton, flat, 1 NO, Lampholder W2 x 4.6 d, Complete apparatus 16mm, luminous pushbutton, blue grade, 1NA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data

Illuminated pushbutton, 16 mm, round, plastic, blue, pushbutton, flat, 1 NO, Lampholder W2 x 4.6 d,

product brand name SIRIUS

product designation Illuminated pushbuttons

design of the product Complete unit round

product type designation 3SB2

Enclosure

number of command points 1

Actuator

design of the actuating element Illuminated pushbutton

principle of operation of the actuating element momentary contact type

product extension optional light source Yes

color of the actuating element blue

material of the actuating element plastic

shape of the actuating element Flat pushbutton
type of unlocking device without
number of switching positions 2
Front ring
product component front ring Yes
design of the front ring Standard
material of the front ring plastic
color of the front ring black
Holder
material of the holder Plastic
Contact block/ lampholder
socket design W2 x 4.6d without lamp
number of lampholders 1
number of switching elements 1
General technical data
product function
? positive opening No
? EMERGENCY STOP function No
product component light source No
type of voltage of the operating voltage AC/DC
protection class IP IP65
vibration resistance according to IEC 60068-2-6 20 ... 200 Hz: 5g
operating frequency maximum 1 000 1/h
mechanical service life (switching cycles) typical 3 000 000
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 07/01/2006
operating voltage rated value 5 ... 60 V
Auxiliary circuit
number of NC contacts for auxilia...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SB2206-0AF01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.