

INDUSTRIAL COMPONENT DATA

3SB2455-0F SIEMENS Contact block, 1 NC, 1 NC, soldering pin connection

Brand: SIEMENS | Manufacturer Part Number: 3SB2455-0F



Manufacturer	SIEMENS
MPN / Reference	3SB2455-0F
Catalog number	24550
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-5B603C5B22
Generated	2026-08-02

Product Overview

Contact block, 1 NC, 1 NC, soldering pin connection
SWITCHING ELEMENT, 1NC, 1NC, SOLDER PIN CONNECTION.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices
--------------	---

Additional Product Information

Technical data
Contact block, 1 NC, 1 NC, soldering pin connection
product brand name SIRIUS
product designation contact block
product type designation 3SB2
Contact block/ lampholder
number of lampholders 0
General technical data
product function positive opening Yes
suitability for integration pushbutton / selector button
type of voltage
? of the operating voltage AC/DC
protection class IP
? of the enclosure IP40

? of the terminal IP00

vibration resistance according to IEC 60068-2-6 20 ... 200 Hz: 5g

reference code according to IEC 81346-2 S

Substance Prohibitance (Date) 07/01/2006

operating voltage

? at AC

- at 50 Hz rated value 5 ... 230 V

- at 60 Hz rated value 5 ... 230 V

? at DC rated value 5 ... 230 V

Auxiliary circuit

number of NC contacts for auxiliary contacts 2

number of NO contacts for auxiliary contacts 0

number of CO contacts for auxiliary contacts 0

operational current at AC-12

? at 24 V rated value 10 A

? at 60 V rated value 10 A

? at 110 V rated value 10 A

? at 230 V rated value 10 A

operational current at AC-15

? at 24 V rated value 4 A

? at 110 V rated value 4 A

? at 230 V rated value 4 A

operational current at DC-12

? at 24 V rated value 6 A

? at 60 V rated value 5 A

? at 110 V rated value 2.5 A

? at 230 V rated value 1 A

operational current at DC-13

? at 24 V rated value 3 A

? at 60 V rated value 1.2 A

? at 110 V rated value 0.7 A

? at 230 V rated value 0.3 A

Connections/ Terminals

type of electrical connection solder pin connectors

Ambient conditions

am...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SB2455-0F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.