


INDUSTRIAL COMPONENT DATA

3SB2455-1C SIEMENS Contact block and lampholder 1 NC, Wedge base W2 x 4.6 d, soldering pin connection

Brand: SIEMENS | Manufacturer Part Number: 3SB2455-1C



Manufacturer	SIEMENS
MPN / Reference	3SB2455-1C
Catalog number	24551
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-789B095ABC
Generated	2026-08-06

Product Overview

Contact block and lampholder 1 NC, Wedge base W2 x 4.6 d, soldering pin connection
Connection element and lamp holder 1NC, Wedge-base W2 x 4.6d.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Commanding and signaling devices**

Additional Product Information

Technical data

Contact block and lampholder 1 NC, Wedge base W2 x 4.6 d, soldering pin connection

product brand name SIRIUS

product designation contact block and lampholder

product type designation 3SB2

Contact block/ lampholder

socket design W2 x 4.6d

number of lampholders 1

General technical data

product function positive opening Yes

product component

? light source No

suitability for integration pushbutton / selector button

type of voltage

? of the operating voltage AC/DC
protection class IP
? of the enclosure IP40
? of the terminal IP00
vibration resistance according to IEC 60068-2-6 20 ... 200 Hz: 5g
reference code according to IEC 81346-2 S
Substance Prohibitance (Date) 07/01/2006
operating voltage
? at AC
- at 50 Hz rated value 5 ... 60 V
- at 60 Hz rated value 5 ... 60 V
? at DC rated value 5 ... 60 V
Auxiliary circuit
number of NC contacts for auxiliary contacts 0
number of NO contacts for auxiliary contacts 1
number of CO contacts for auxiliary contacts 0
operational current at AC-12
? at 24 V rated value 10 A
? at 60 V rated value 10 A
? at 110 V rated value 10 A
? at 230 V rated value 10 A
operational current at AC-15
? at 24 V rated value 4 A
? at 110 V rated value 4 A
? at 230 V rated value 4 A
operational current at DC-12
? at 24 V rated value 6 A
? at 60 V rated value 5 A
? at 110 V rated value 2.5 A
? at 230 V rated value 1 A
operational current at DC-13
? at 24 V rated value 3 A
? at 60 V rated value 1.2 A
? at 110 V rated value 0.7 A
? at 230 V rated value...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SB2455-1C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.