

INDUSTRIAL COMPONENT DATA

3SE2243-0XX SIEMENS Safety position switch with separate actuator Molded-plastic enclosure lateral and face-..

Brand: SIEMENS | Manufacturer Part Number: 3SE2243-0XX



Manufacturer	SIEMENS
MPN / Reference	3SE2243-0XX
Catalog number	22430
Category	Position switch with separate actuator
Minimum order	1 Pcs
Document ID	EO-112A0D32AC
Generated	2026-08-03

Product Overview

Safety position switch with separate actuator Molded-plastic enclosure lateral and face-end Slow-action contacts 1 NO+2 NC, 3 x (M20 x 1.5) Pull-out force 30 N Supplied without actuator

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

Safety position switch with separate actuator Molded-plastic enclosure lateral and face-end Slow-action contacts 1 NO+2 NC, 3 x (M20 x 1.5) Pull-out force 30 N Supplied without actuator

product brand name SIRIUS

product designation safety position switch

product type designation 3SE22

suitability for use safety switch Yes

General technical data

insulation voltage rated value 500 V

surge voltage resistance rated value 6 kV

protection class IP IP67

mechanical service life (switching cycles) typical 1 000 000

thermal current 10 A

reference code according to IEC 81346-2 B

active principle mechanical
Substance Prohibitance (Date) 07/01/2006
length of the sensor 90 mm
width of the sensor 52 mm
design of the switching contact mechanical
operating frequency rated value 60 ... 50 Hz
number of NC contacts for auxiliary contacts 2
number of NO contacts for auxiliary contacts 1
operational current at AC-15
? at 230 V rated value 4 A
operational current at DC-13
? at 24 V rated value 4 A
design of the interface for safety-related communication without
Enclosure
design of the housing wide
material of the enclosure glass fiber reinforced thermoplast
coating of the enclosure Other types
design of the housing according to standard No
Drive Head
design of the actuating element without
design of the switching function positive opening
circuit principle slow-action contacts
number of switching contacts safety-related 1
Connections/ Terminals
type of electrical connection screw-ty...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE2243-0XX with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.