

## INDUSTRIAL COMPONENT DATA

# 3SE2283-0GA44 SIEMENS Hinge switch Molded-plastic enclosure with stainless steel hinge 2 NC/1 NO, for 40 mm ..

Brand: SIEMENS | Manufacturer Part Number: 3SE2283-0GA44



|                 |               |
|-----------------|---------------|
| Manufacturer    | SIEMENS       |
| MPN / Reference | 3SE2283-0GA44 |
| Catalog number  | 22830         |
| Category        | Hinge switch  |
| Minimum order   | 1 Pcs         |
| Document ID     | EO-A5C8373E70 |
| Generated       | 2026-08-04    |

## Product Overview

Hinge switch Molded-plastic enclosure with stainless steel hinge 2 NC/1 NO, for 40 mm profiles Supplied with additional hinge and fixing material Actuating angle 4°

INTERR. SIRIUS HINGE INSULATING MATERIAL BOX WITH 2NC/1NA STAINLESS STEEL HINGE, FOR 40MM PROFILES, SUPPLY WITH ADDITIONAL HINGE AND FIXING MATERIAL

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

## Additional Product Information

## Technical data

Hinge switch Molded-plastic enclosure with stainless steel hinge 2 NC/1 NO, for 40 mm profiles Supplied with additional hinge and fixing material Actuating angle 4°

product brand name SIRIUS

product designation safety position switch

product type designation 3SE228

suitability for use safety switch Yes

## General technical data

product function positive opening Yes

insulation voltage rated value 250 V

surge voltage resistance rated value 4 kV

protection class IP IP65

shock resistance 30g / 18 ms  
vibration resistance 10 ... 200 Hz: 20g  
mechanical service life (switching cycles) typical 1 000 000  
thermal current 2.5 A  
reference code according to IEC 81346-2 B  
active principle mechanical  
Substance Prohibitance (Date) 07/01/2006  
length of the sensor 92 mm  
width of the sensor 111.5 mm  
design of the switching contact mechanical  
number of NC contacts for auxiliary contacts 2  
number of NO contacts for auxiliary contacts 1  
operational current at AC-15  
? at 125 V rated value 4.2 A  
? at 230 V rated value 2 A  
operational current at DC-13  
? at 24 V rated value 1 A  
design of the interface for safety-related communication without  
Enclosure  
design of the housing special design  
material of the enclosure glass fiber reinforced thermoplast  
coating of the enclosure none  
design of the housing according to standard No  
Drive Head  
design of the actuating element rotary actuator  
design of the switching function positive opening  
circuit principle slow-action contacts  
number of switching c...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE2283-0GA44 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.