

INDUSTRIAL COMPONENT DATA

3SE2283-0GA44 SIEMENS Hinge switch Molded-plastic enclosure with stainless steel hinge 2 NC/1 NO, for 40 mm ..

Brand: SIEMENS | Manufacturer Part Number: 3SE2283-0GA44



Manufacturer	SIEMENS
MPN / Reference	3SE2283-0GA44
Catalog number	22830
Category	Hinge switch
Minimum order	1 Pcs
Document ID	EO-A5C8373E70
Generated	2026-08-06

Product Overview

Hinge switch Molded-plastic enclosure with stainless steel hinge 2 NC/1 NO, for 40 mm profiles Supplied with additional hinge and fixing material Actuating angle 4°

INTERR. SIRIUS HINGE INSULATING MATERIAL BOX WITH 2NC/1NA STAINLESS STEEL HINGE, FOR 40MM PROFILES, SUPPLY WITH ADDITIONAL HINGE AND FIXING MATERIAL

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

Hinge switch Molded-plastic enclosure with stainless steel hinge 2 NC/1 NO, for 40 mm profiles Supplied with additional hinge and fixing material Actuating angle 4°

product brand name SIRIUS

product designation safety position switch

product type designation 3SE228

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 250 V

surge voltage resistance rated value 4 kV

protection class IP IP65

shock resistance 30g / 18 ms
vibration resistance 10 ... 200 Hz: 20g
mechanical service life (switching cycles) typical 1 000 000
thermal current 2.5 A
reference code according to IEC 81346-2 B
active principle mechanical
Substance Prohibitance (Date) 07/01/2006
length of the sensor 92 mm
width of the sensor 111.5 mm
design of the switching contact mechanical
number of NC contacts for auxiliary contacts 2
number of NO contacts for auxiliary contacts 1
operational current at AC-15
? at 125 V rated value 4.2 A
? at 230 V rated value 2 A
operational current at DC-13
? at 24 V rated value 1 A
design of the interface for safety-related communication without
Enclosure
design of the housing special design
material of the enclosure glass fiber reinforced thermoplast
coating of the enclosure none
design of the housing according to standard No
Drive Head
design of the actuating element rotary actuator
design of the switching function positive opening
circuit principle slow-action contacts
number of switching c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE2283-0GA44 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.