

INDUSTRIAL COMPONENT DATA

3SE2932-1AB20 SIEMENS Momentary-contact foot switch, 2-pedal without cover, without latching, Metal enclosur..

Brand: SIEMENS | Manufacturer Part Number: 3SE2932-1AB20



Manufacturer	SIEMENS
MPN / Reference	3SE2932-1AB20
Catalog number	29321
Category	Foot switch
Minimum order	1 Pcs
Document ID	EO-D95D4791EA
Generated	2026-08-03

Product Overview

Momentary-contact foot switch, 2-pedal without cover, without latching, Metal enclosure IP65, slow-action contacts 2 NO+2 NC Cable entry M25 x 1.5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

Momentary-contact foot switch, 2-pedal without cover, without latching, Metal enclosure IP65, slow-action contacts 2 NO+2 NC Cable entry M25 x 1.5

product brand name SIRIUS

product designation momentary-contact foot switch

product type designation 3SE29

suitability for use safety switch No

General technical data

protection class IP IP65

reference code according to IEC 81346-2 S

Substance Prohibitance (Date) 07/01/2006

number of switching steps 1

number of the actuation pedals 2

minimum actuating force in directions of actuation 20 N

number of NC contacts for auxiliary contacts 2
number of NO contacts for auxiliary contacts 2
operational current at AC-15
? at 230 V rated value 6 A
? at 400 V rated value 6 A
operational current at DC-13
? at 24 V rated value 3 A
? at 250 V rated value 0.25 A
Enclosure
material of the enclosure metal
color
? of the enclosure black
? of the enclosure top part grey
Actuator
product feature
? interlock No
? latching No
Safety related data
B10 value with high demand rate according to SN 31920 1 000 000
proportion of dangerous failures
? with low demand rate according to SN 31920 50 %
? with high demand rate according to SN 31920 50 %
failure rate [FIT] with low demand rate according to SN 31920 100 FIT
T1 value for proof test interval or service life according to IEC 61508 20 y
cable entry type M25 x 1.5
Ambient conditions
ambient temperature during operation -25 ... +80 °C
Installation/ mounting/ dimensions
height 68 mm
width 193 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE2932-1AB20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.