

INDUSTRIAL COMPONENT DATA

3SE5000-0AA11-1AJ0 SIEMENS twist lever for position switch 3SE51 Stainless steel lever, Form A 27 mm long wi..

Brand: SIEMENS | Manufacturer Part Number: 3SE5000-0AA11-1AJ0



Manufacturer	SIEMENS
MPN / Reference	3SE5000-0AA11-1AJ0
Catalog number	50000
Category	Drive head for position switches/hinge switches
Minimum order	1 Pcs
Document ID	EO-55FE3E0CBC
Generated	2026-08-06

Product Overview

twist lever for position switch 3SE51 Stainless steel lever, Form A 27 mm long with plastic roller 19 mm functional at -40 °C ROLLER LEVER FOR INTERRUPT. OF POSITION 3SE51 PAL. STAINLESS STEEL. 27MM LONG., WITH PLASTIC ROLLER 19MM, FUNCTIONALITY AT -40 GR.. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

twist lever for position switch 3SE51 Stainless steel lever, Form A 27 mm long with plastic roller 19 mm functional at -40 °C

product brand name SIRIUS

product designation actuator for part-turn actuator

product type designation 3SE5

General technical data

product function positive opening Yes

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

? for railway applications according to EN 61373 Category 1, Class B

vibration resistance

? according to IEC 60068-2-6 0.35 mm/5g

? for railway applications according to EN 61373 Category 1, Class B

mechanical service life (switching cycles) typical 15 000 000
reference code according to IEC 81346-2 T
active principle mechanical
Substance Prohibitance (Date) 07/01/2006
design of the interface for safety-related communication without
Enclosure
coating of the enclosure Other types
Drive Head
design of the actuating element Twist lever, high-grade steel lever, 27 mm long, step 9 mm, plastic roller 19 mm
standard-compliant actuator head EN 50041, design A
shape of the switch head roller
outer diameter of the switch head 19 mm
Communication/ Protocol
design of the interface without
Ambient conditions
ambient temperature
? during operation -40 ... +85 °C
? during storage -40 ... +90 °C
explosion protection category for dust none
Installation/ mounting/ dimensions
mounting position any
fastening method screw fixing
Certificates/ approvals
Downloads and manuals
General Product Approval
Confirmation
KC
Declaration of Conf...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5000-0AA11-1AJ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.