

INDUSTRIAL COMPONENT DATA

3SE5000-0AA22 SIEMENS twist lever for position switch

3SE52 Metal lever, Form A 21 mm long Stainless steel r..

Brand: SIEMENS | Manufacturer Part Number: 3SE5000-0AA22



Manufacturer	SIEMENS
MPN / Reference	3SE5000-0AA22
Catalog number	50000
Category	Drive head for position switches/hinge switches
Minimum order	1 Pcs
Document ID	EO-559688EF32
Generated	2026-08-05

Product Overview

twist lever for position switch 3SE52 Metal lever, Form A 21 mm long Stainless steel roller 19 mm according to EN 50047 SIRIUS Int. position, accessory 3SE51/52, metal lever 21mm long., stainless steel roller. 19mm. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

twist lever for position switch 3SE52 Metal lever, Form A 21 mm long Stainless steel roller 19 mm according to EN 50047

product brand name SIRIUS

product designation actuator for part-turn actuator

product type designation 3SE5

manufacturer's article number

? of the supplied operating lever 3SE5000-0AA22

General technical data

product function positive opening Yes

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance

? according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 15 000 000
reference code according to IEC 81346-2 T
active principle mechanical
Substance Prohibitance (Date) 07/01/2006
design of the interface for safety-related communication without
Enclosure
coating of the enclosure Other types
Drive Head
design of the actuating element Twist lever, metal lever, 21 mm long, straight, high-grade steel roller 19 mm
standard-compliant actuator head EN 50047, design A
shape of the switch head roller
outer diameter of the switch head 19 mm
Communication/ Protocol
design of the interface without
Ambient conditions
ambient temperature
? during operation -25 ... +85 °C
? during storage -40 ... +90 °C
explosion protection category for dust none
Installation/ mounting/ dimensions
mounting position any
fastening method screw fixing
Certificates/ approvals
Downloads and manuals
General Product Approval
Confirmation
KC
Declaration of Conformity Test Certificates other
UK Declaration of Conformity
Type Test...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5000-0AA22 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.