

INDUSTRIAL COMPONENT DATA

3SE5000-0AA24 SIEMENS twist lever for position switch 3SE51/52 Metal lever, 30 mm long with plastic roller 1..

Brand: SIEMENS | Manufacturer Part Number: 3SE5000-0AA24



Manufacturer	SIEMENS
MPN / Reference	3SE5000-0AA24
Catalog number	50000
Category	Drive head for position switches/hinge switches
Minimum order	1 Pcs
Document ID	EO-2AE15C4CE9
Generated	2026-08-06

Product Overview

twist lever for position switch 3SE51/52 Metal lever, 30 mm long with plastic roller 19 mm Roller on cover Rotated by 180°
Rear of lever mountable

ROLLER LEVER FOR INTERRUPT. POSITION 3SE51 /52 METAL LEVER 30MM LONG WITH PLASTIC ROLLER 19MM,
CAN BE MOUNTED ON LID (ROTATED 180 DEGREES)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

twist lever for position switch 3SE51/52 Metal lever, 30 mm long with plastic roller 19 mm Roller on cover Rotated by 180°
Rear of lever mountable

product brand name SIRIUS

product designation actuator for part-turn actuator

product type designation 3SE5

manufacturer's article number

? of the supplied operating lever 3SE5000-0AA24

General technical data

product function positive opening Yes

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance

? according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 15 000 000

reference code according to IEC 81346-2 T

active principle mechanical

Substance Prohibitance (Date) 07/01/2006

design of the interface for safety-related communication without

Enclosure

coating of the enclosure Other types

Drive Head

design of the actuating element Twist lever, metal lever, 30 mm long, straight, plastic roller 19 mm

standard-compliant actuator head EN 50041, design A

shape of the switch head roller

outer diameter of the switch head 19 mm

Communication/ Protocol

design of the interface without

Ambient conditions

ambient temperature

? during operation -25 ... +85 °C

? during storage -40 ... +90 °C

explosion protection category for dust none

Installation/ mounting/ dimensions

mounting position any

fastening method screw fixing

Certificates/ approvals

Downloads and manuals

General Product Approval

Confirmation

KC

Declaration of Conformity Test Certificates other

UK Declaration of Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5000-0AA24 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.