

INDUSTRIAL COMPONENT DATA

3SE5000-0AA25 SIEMENS twist lever for position switch

3SE52 Metal lever, 21 mm long Plastic roller 30 mm

Brand: SIEMENS | Manufacturer Part Number: 3SE5000-0AA25



Manufacturer	SIEMENS
MPN / Reference	3SE5000-0AA25
Catalog number	50000
Category	Drive head for position switches/hinge switches
Minimum order	1 Pcs
Document ID	EO-F8CEFEDEBF
Generated	2026-08-06

Product Overview

twist lever for position switch 3SE52 Metal lever, 21 mm long Plastic roller 30 mm
SIRIUS Int. position, accessory 3SE51/52, metal lever 21mm long., plastic roller 30mm. Manufactured to order.
Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

twist lever for position switch 3SE52 Metal lever, 21 mm long Plastic roller 30 mm

product brand name SIRIUS

product designation actuator for part-turn actuator

product type designation 3SE5

manufacturer's article number

? of the supplied operating lever 3SE5000-0AA25

General technical data

product function positive opening Yes

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance

? according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 15 000 000
reference code according to IEC 81346-2 T
active principle mechanical
Substance Prohibitance (Date) 07/01/2006
design of the interface for safety-related communication without
Enclosure
coating of the enclosure Other types
Drive Head
design of the actuating element Twist lever, metal lever, 21 mm long, straight, plastic roller 30 mm
standard-compliant actuator head EN 50047, design A
shape of the switch head roller
outer diameter of the switch head 30 mm
Communication/ Protocol
design of the interface without
Ambient conditions
ambient temperature
? during operation -25 ... +85 °C
? during storage -40 ... +90 °C
explosion protection category for dust none
Installation/ mounting/ dimensions
mounting position any
fastening method screw fixing
Certificates/ approvals
Downloads and manuals
General Product Approval
Confirmation
KC
Declaration of Conformity Test Certificates other
UK Declaration of Conformity
Type Test Certificates/Test Report
Confirmation
Further...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5000-0AA25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.