

INDUSTRIAL COMPONENT DATA

3SE5000-0AA26 SIEMENS twist lever for position switch 3SE51/52 Metal lever, 30 mm long with Plastic roller 3..

Brand: SIEMENS | Manufacturer Part Number: 3SE5000-0AA26



Manufacturer	SIEMENS
MPN / Reference	3SE5000-0AA26
Catalog number	50000
Category	Drive head for position switches/hinge switches
Minimum order	1 Pcs
Document ID	EO-D16F50671A
Generated	2026-08-06

Product Overview

twist lever for position switch 3SE51/52 Metal lever, 30 mm long with Plastic roller 30 mm Roller can be mounted on cover
Rotated by 180° Rear of lever mountable
ROLLER LEVER FOR INTERRUPT. POSITION 3SE51 /52 METAL LEVER 30MM LONG WITH PLASTIC ROLLER 19MM,
ROLLER MOUNTED TO THE REVERSE (ROTATED 180 DEGREES, TO THE BACK OF THE LEVER). Manufactured to
order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

twist lever for position switch 3SE51/52 Metal lever, 30 mm long with Plastic roller 30 mm Roller can be mounted on cover
Rotated by 180° Rear of lever mountable
product brand name SIRIUS
product designation actuator for part-turn actuator
product type designation 3SE5
manufacturer's article number
? of the supplied operating lever 3SE5000-0AA26
General technical data
product function positive opening Yes
shock resistance

? according to IEC 60068-2-27 30g / 11 ms
vibration resistance
? according to IEC 60068-2-6 0.35 mm/5g
mechanical service life (switching cycles) typical 15 000 000
reference code according to IEC 81346-2 T
active principle mechanical
Substance Prohibitance (Date) 07/01/2006
design of the interface for safety-related communication without
Enclosure
coating of the enclosure Other types
Drive Head
design of the actuating element Twist lever, metal lever, 30 mm long, straight, plastic roller 30 mm
standard-compliant actuator head EN 50041, design A
shape of the switch head roller
outer diameter of the switch head 30 mm
Communication/ Protocol
design of the interface without
Ambient conditions
ambient temperature
? during operation -25 ... +85 °C
? during storage -40 ... +90 °C
explosion protection category for dust none
Installation/ mounting/ dimensions
mounting position any
fastening method screw fixing
Certificates/ approvals
Downloads and manuals
General Product Approval
Confirmation
KC
Declaration of Conformity Test Certificates other
UK De...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5000-0AA26 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.