

INDUSTRIAL COMPONENT DATA

3SE5000-0AA55 SIEMENS Adjustable-length Twist lever for position switch 3SE51/52 Metal lever 100 mm long Pla..

Brand: SIEMENS | Manufacturer Part Number: 3SE5000-0AA55



Manufacturer	SIEMENS
MPN / Reference	3SE5000-0AA55
Catalog number	50000
Category	Drive head for position switches/hinge switches
Minimum order	1 Pcs
Document ID	EO-C47A5968B0
Generated	2026-08-04

Product Overview

Adjustable-length Twist lever for position switch 3SE51/52 Metal lever 100 mm long Plastic roller 30 mm SIRIUS Int. position, accessory 3SE51/52, lever adjust. metal 100mm long., plastic roller 30mm. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

Adjustable-length Twist lever for position switch 3SE51/52 Metal lever 100 mm long Plastic roller 30 mm

product brand name SIRIUS

product designation actuator for part-turn actuator

product type designation 3SE5

manufacturer's article number

? of the supplied operating lever 3SE5000-0AA55

suitability for use safety switch No

General technical data

product function positive opening No

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance

? according to IEC 60068-2-6 0.35 mm/5g
mechanical service life (switching cycles) typical 15 000 000
reference code according to IEC 81346-2 T
active principle mechanical
Substance Prohibitance (Date) 07/01/2006
design of the interface for safety-related communication without
Enclosure
coating of the enclosure Other types
Drive Head
design of the actuating element Adjustable twist lever, adjustable-length metal lever, plastic roller 30 mm
shape of the switch head roller
outer diameter of the switch head 30 mm
Communication/ Protocol
design of the interface without
Ambient conditions
ambient temperature
? during operation -25 ... +85 °C
? during storage -40 ... +90 °C
explosion protection category for dust none
Installation/ mounting/ dimensions
mounting position any
fastening method screw fixing
Certificates/ approvals
Downloads and manuals
General Product Approval
Confirmation
KC
Declaration of Conformity Test Certificates other
UK Declaration of Conformity
Type Test Certificates/Test Report
Confirma...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5000-0AA55 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.