

INDUSTRIAL COMPONENT DATA

3SE5000-0AE01 SIEMENS Actuator head for position switch 3SE51 Roller lever Metal lever and Plastic roller 22..

Brand: SIEMENS | Manufacturer Part Number: 3SE5000-0AE01



Manufacturer	SIEMENS
MPN / Reference	3SE5000-0AE01
Catalog number	50000
Category	Drive head for position switches/hinge switches
Minimum order	1 Pcs
Document ID	EO-6B2AF6A7F2
Generated	2026-08-05

Product Overview

Actuator head for position switch 3SE51 Roller lever Metal lever and Plastic roller 22 mm
SIRIUS Int. position, accessory 3SE51/52, single lever roller actuator with metal lever and 22mm plastic roller.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

Actuator head for position switch 3SE51 Roller lever Metal lever and Plastic roller 22 mm

product brand name SIRIUS

product designation actuator head for position switch

product type designation 3SE5

manufacturer's article number

? of the supplied actuator head for position switches 3SE5000-0AE01

General technical data

product function positive opening Yes

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance

? according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 15 000 000

material of the enclosure of the switch head plastic
reference code according to IEC 81346-2 T
active principle mechanical
Substance Prohibitance (Date) 07/01/2006
minimum actuating force in directions of actuation 10 N
design of the interface for safety-related communication without
Enclosure
coating of the enclosure Other types
Drive Head
design of the actuating element Roller lever, metal lever, plastic roller
standard-compliant actuator head EN 50041
shape of the switch head roller
outer diameter of the switch head 22 mm
Communication/ Protocol
design of the interface without
Ambient conditions
ambient temperature
? during operation -25 ... +85 °C
? during storage -40 ... +90 °C
explosion protection category for dust none
Installation/ mounting/ dimensions
mounting position any
fastening method lockable plug-in fixing
Certificates/ approvals
Downloads and manuals
General Product Approval Declaration of Conformity
Confirmation...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5000-0AE01 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.