

INDUSTRIAL COMPONENT DATA

3SE5000-0NA00 SIEMENS Contact block for position switch 3SE51/52 1 NO/1 NC quick action contact Short stroke

Brand: SIEMENS | Manufacturer Part Number: 3SE5000-0NA00



Manufacturer	SIEMENS
MPN / Reference	3SE5000-0NA00
Catalog number	50000
Category	Accessories/spare parts for position switches
Minimum order	1 Pcs
Document ID	EO-5D24A96255
Generated	2026-08-05

Product Overview

Contact block for position switch 3SE51/52 1 NO/1 NC quick action contact Short stroke
SIRIUS Int. position, accessory 3SE51/52, block of contacts acc. abrupt 1NA/1NC, short stroke. Manufactured to order.
Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

Contact block for position switch 3SE51/52 1 NO/1 NC quick action contact Short stroke

product brand name SIRIUS

product designation contact

product type designation 3SE5

General technical data

product function positive opening Yes

insulation voltage rated value 400 V

degree of pollution class 3

surge voltage resistance rated value 6 kV

protection class IP IP00

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance

? according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 15 000 000

electrical endurance (switching cycles) at AC-15 at 230 V typical 100 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 10 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000

thermal current 10 A

reference code according to IEC 81346-2 S

continuous current of the C characteristic MCB 1 A; for a short-circuit current smaller than 400 A

continuous current of the quick DIAZED fuse link 10 A; for a short-circuit current smaller than 400 A

continuous current of the DIAZED fuse link gG 6 A

active principle mechanical

repeat accuracy 0.1 mm

Substance Prohibitance (Date) 07/01/2006

width of the sensor 25 mm

operating frequency rated value 50 ... 60 Hz

number of NC contacts for auxiliary contacts 1

number of NO contacts for auxiliary contacts 1

operational current at AC-15

? at 24 V rated value 6 A

?...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5000-0NA00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.