

INDUSTRIAL COMPONENT DATA

3SE5114-0LH01-1AE3 SIEMENS Position switch with lever Metal enclosure 40 mm according to EN 50041, 1 NO/2 NC..

Brand: SIEMENS | Manufacturer Part Number: 3SE5114-0LH01-1AE3



Manufacturer	SIEMENS
MPN / Reference	3SE5114-0LH01-1AE3
Catalog number	50041
Category	End switch
Minimum order	1 Pcs
Document ID	EO-2624B1DDB9
Generated	2026-08-05

Product Overview

Position switch with lever Metal enclosure 40 mm according to EN 50041, 1 NO/2 NC quick action contacts, with M12 connector, 5-pole, fixed pin assignment Pin1=21, Pin4=22 Pin2=31, Pin5=32, Pin3=PE. Rotary actuator right and/or left adjustable, metal lever 27 mm long and plastic roller 19 mm. Suitable for connection to all SIMATIC ET200* compact block I/O modules.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

Position switch with lever Metal enclosure 40 mm according to EN 50041, 1 NO/2 NC quick action contacts, with M12 connector, 5-pole, fixed pin assignment Pin1=21, Pin4=22 Pin2=31, Pin5=32, Pin3=PE. Rotary actuator right and/or left adjustable, metal lever 27 mm long and plastic roller 19 mm. Suitable for connection to all SIMATIC ET200* compact block I/O modules.

product brand name SIRIUS

product designation Mechanical safety switches

product type designation 3SE5

manufacturer's article number

? of the supplied basic switch 3SE5114-0LA00-1AE3

? of the supplied actuator head for position switches 3SE5000-0AH00

? of the supplied operating lever 3SE5000-0AA01

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 125 V

degree of pollution class 3

surge voltage resistance rated value 1.5 kV

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 15 000 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 10 000 000

Electrical operating cycles in one hour with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 6 000

thermal current 4 A

material of the enclosure of the switch head plastic

reference code according to IEC 81346-2 B

continuous current of the C characteristic MCB 1....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5114-0LH01-1AE3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.