

INDUSTRIAL COMPONENT DATA

3SE5114-0QV10-1AE3 SIEMENS Safety position switch with separate actuator Metal enclosure 40 mm, with M12 con..

Brand: SIEMENS | Manufacturer Part Number: 3SE5114-0QV10-1AE3



Manufacturer	SIEMENS
MPN / Reference	3SE5114-0QV10-1AE3
Catalog number	10000
Category	End switch
Minimum order	1 Pcs
Document ID	EO-4D068CF503
Generated	2026-08-06

Product Overview

Safety position switch with separate actuator Metal enclosure 40 mm, with M12 connector, plastic 5-pole, Max. 125 V, 4 A, 5 directions of approach. Slow-action contacts 2 NC connected, Pin1=21, Pin4=22, Pin2=31, Pin5=32 Pin3=PE.. Suitable for connection to all SIMATIC ET200* compact block I/O modules. The matching separate Actuator 3SE5000-0AV../W..must be ordered separately.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays**

Additional Product Information

Technical data

Safety position switch with separate actuator Metal enclosure 40 mm, with M12 connector, plastic 5-pole, Max. 125 V, 4 A, 5 directions of approach. Slow-action contacts 2 NC connected, Pin1=21, Pin4=22, Pin2=31, Pin5=32 Pin3=PE.. Suitable for connection to all SIMATIC ET200* compact block I/O modules. The matching separate Actuator 3SE5000-0AV../W..must be ordered separately.

product brand name SIRIUS

product designation Mechanical safety switches

product type designation 3SE5

manufacturer's article number

? of the optional actuators 3SE5000-0AV01 standard actuator, 3SE5000-0AV02 actuator with vertical mounting, 3SE5000-0AV03 actuator with horizontal mounting, 3SE5000-0AV04 radius actuator left, 3SE5000-0AV05 universal actuator, 3SE5000-0AV06 radius actuator right, 3SE5000-0AV07 heavy-duty actuator, 3SE5000-0AW11 plastic actuator,

3SE5000-0AW21 stainless steel actuator

suitability for use safety switch Yes

General technical data

product function positive opening Yes

insulation voltage rated value 125 V

degree of pollution class 3

surge voltage resistance rated value 1.5 kV

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance according to IEC 60068-2-6 0.35 mm/5g

mechanical service life (switching cycles) typical 1 000 000

electrical endurance (switching cycles) with contactor 3RH11, 3RT1016, 3RT1017, 3RT1024, 3RT1025, 3RT1026 typical 1 000 000

Electrical operating cycles in one hour with contactor 3RH11,...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5114-0QV10-1AE3 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.