

INDUSTRIAL COMPONENT DATA

3SE5122-0AA00-1CA0 SIEMENS enclosure with increased corrosion protection for position switch 3SE51 56 mm wid..

Brand: SIEMENS | Manufacturer Part Number: 3SE5122-0AA00-1CA0



Manufacturer	SIEMENS
MPN / Reference	3SE5122-0AA00-1CA0
Catalog number	51220
Category	Accessories/spare parts for position switches
Minimum order	1 Pcs
Document ID	EO-2D1CA430AC
Generated	2026-08-04

Product Overview

enclosure with increased corrosion protection for position switch 3SE51 56 mm wide, Metal with cover, turquoise Device connection 3 x (M20 x 1.5)

SIRIUS Int. position, plastic box 56mm, connection 3X (M20X1,5), empty box, increased corrosion protection. Manufactured to order. Non-Cancelable Non-Returnable.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path SIEMENS > CONTROL AND CONTACTORS > Limit Switches and safety relays

Additional Product Information

Technical data

enclosure with increased corrosion protection for position switch 3SE51 56 mm wide, Metal with cover, turquoise Device connection 3 x (M20 x 1.5)

product designation enclosure with increased corrosion protection for standard position switch, metal, 54 mm wide, cover turquoise

General technical data

insulation voltage rated value 400 V

degree of pollution class 3

protection class IP IP66/IP67

shock resistance

? according to IEC 60068-2-27 30g / 11 ms

vibration resistance according to IEC 60068-2-6 0.35 mm/5g

reference code according to IEC 81346-2 U
active principle mechanical
Substance Prohibitance (Date) 07/01/2006
length of the sensor 85.7 mm
width of the sensor 56 mm
design of the interface for safety-related communication without
Enclosure
design of the housing block, wide
material of the enclosure metal
coating of the enclosure cathodic dip coating
design of the housing according to standard No
Drive Head
design of the actuating element Other, without, empty enclosure
cable entry type 3x (M20 x 1.5)
Communication/ Protocol
design of the interface without
Ambient conditions
ambient temperature
? during operation -25 ... +85 °C
? during storage -40 ... +90 °C
explosion protection category for dust none
Installation/ mounting/ dimensions
mounting position any
fastening method screw fixing
Certificates/ approvals
Downloads and manuals
General Product Approval
Confirmation
Functional Safety/Safety of Machinery Declaration of Conformity Test Certificates other....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send SIEMENS / 3SE5122-0AA00-1CA0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.